

1 LOCATION OF WATER WELL: Fraction $\frac{1}{4}$ C-SE $\frac{1}{4}$ Section Number 33 Township Number T 33 S Range Number R 38 E/W

Distance and direction from nearest town or city street address of well if located within city? From Feterita go 2mi South 1 1/2mi East 1/2mi Northeast to location.

2 WATER WELL OWNER: Dewey Moser Anadarko Production
RR#, St. Address, Box #: 607 S. Polk
City, State, ZIP Code: Hugoton, Kansas 67951
Board of Agriculture, Division of Water Resources
Application Number: T -84-328

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 260 ft. ELEVATION:

	Depth(s) Groundwater Encountered 1. 119 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 141 ft. below land surface measured on mo/day/yr 6/14/84
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield 60 gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter 9 in. to 260 ft., and in. to ft.	
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well	
Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes No	

5 TYPE OF BLANK CASING USED: 3 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
2 PVC 4 ABS 7 Fiberglass Threaded

Blank casing diameter 5 in. to 183 ft., Dia. in. to ft., Dia. in. to ft.

Casing height above land surface 28 in., weight 2.85 lbs./ft. Wall thickness or gauge No. 265

TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 180 ft. to 260 ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 80 ft. to 260 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage

Direction from well? Northeast of water well. How many feet? 100'

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	0 / surface			
2	28	0 / sandy clay			
28	42	0 / fine sand			
42	82	0 / medium to large sand			
82	135	35 gravel with clay mixed			
135	159	0 / sandy clay			
159	185	0 / red clay			
185	210	fine sand with clay streaks			
210	235	0 / sandy clay			
235	248	0 / medium to large sand			
248	260	0 / yellow and red clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) June 14, 1984 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 118 This Water Well Record was completed on (mo/day/yr) June 27, 1984

under the business name of Carlile Water Well Service, Inc. by (signature)

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

33

R

38

E/W

SEC.

33

C

1/4

SE

1/4