

1 LOCATION OF WATER WELL: County: Stevens		Fraction SE 1/4 NE 1/4 SE 1/4		Section Number 25	Township Number T 33 S	Range Number R 39 E/W
Distance and direction from nearest town or city street address of well if located within city? From west side of Feterita - 1 Mile SW on Hwy. 25, 1/2 Mile South, 1,475 Ft. North & 10 Ft. West						
2 WATER WELL OWNER: Seaboard Farms, Inc.		Board of Agriculture, Division of Water Resources				
RR#, St. Address, Box # : P. O. Box 1029		Application Number: 41,391				
City, State, ZIP Code : Hugoton, Kansas 67951						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 405 ft. ELEVATION:				
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.				
		WELL'S STATIC WATER LEVEL: 135 ft. below land surface measured on mo/day/yr 1-20-96				
		Pump test data: Well water was ft. after hours pumping gpm				
		Est. Yield gpm: Well water was ft. after hours pumping gpm				
		Bore Hole Diameter: 30 in. to 405 ft., and in. to ft.				
		WELL WATER TO BE USED AS:				
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below)				
		Was a chemical/bacteriological sample submitted to Department? Yes.....No..... X; If yes, mo/day/yr sample was submitted				
		Water Well Disinfected? Yes No X				
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped				
1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought iron 8 Concrete tile Welded X 6 Asbestos-Cement 9 Other (specify below) Threaded				
Blank casing diameter: 16 in. to 340 ft., Dia. in. to ft., Dia. in. to ft.						
Casing height above land surface: 12 in., weight 42.05 lbs./ft. Wall thickness or gauge No. 250						
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement				
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)				
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)						
SCREEN-PERFORATED INTERVALS: From 340 ft. to 405 ft., From ft. to ft.						
GRAVEL PACK INTERVALS: From 50 ft. to 405 ft., From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other						
Grout Intervals: From 0 ft. to 50 ft., From ft. to ft., From ft. to ft.						
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well				
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage N/A						
Direction from well?		How many feet?				
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	
		See attached log				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-20-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/yr) 1-26-96 under the business name of Minter-Wilson Drilling Co., Inc. by (signature) <i>Nora Keller</i>						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.						