


1 LOCATION OF WATER WELL: County: STEVENS		Fraction NE 1/4 NE 1/4 NE 1/4	Section Number 27	Township Number T 33 S	Range Number R 39 E/W				
Distance and direction from nearest town or city street address of well if located within city? FROM FETEITA 3-1/4 MILES WEST & SOUTH IN THE FIELD.									
2 WATER WELL OWNER: MORGAN FAMILY LTD. PARTNERSHIP, C/O GARY L. BAKER RR#, St. Address, Box #: 827 E. ELEVENTH City, State, ZIP Code: HUGOTON, KS 67951 Board of Agriculture, Division of Water Resources Application Number: 42,326									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL 382 ft. ELEVATION: Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 112 ft. below land surface measured on mo/day/yr 10/7/96 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 26 in. to 382 ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No							
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X Blank casing diameter 16 in. to 382 ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface 12 in. weight 42.5 lbs./ft. Wall thickness or gauge No. 250 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From SCREEN 220 ft. to 360 ft. From PERF. 360 ft. to 380 ft. GRAVEL PACK INTERVALS: From 20 ft. to 382 ft. From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) CROPLAND-NOTHING IMMEDIATE VICINITY Direction from well? How many feet?									
FROM		TO		LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS	
0		180		SURFACE, SAND & CLAY					
180		240		BROWN CLAY W/SAND					
240		380		FINE TO MED. SAND					
380		385		RED CLAY					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/7/96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 225 This Water Well Record was completed on (mo/day/yr) 6/8/97 under the business name of KTM DRILLING, INC. by (signature) [Signature]									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.									