	Section Number Township Number Range Number
Distance and direction from nearest town or city APPROX. 8 MILES WEST. 2 MILES NORTH & 1/4 EAST O	street address of well if located within city? F HUGOTON
WATER WELL OWNER: LESTER. BEVERLY RR#. St. Address, Box # : 1200 S ADAMS	Board of Agriculture. Division of Water Resources
City, State, ZIP code : HUGOTON, KS 67951	Application Number: 42,515
	e) Groundwater Encountered 1. 0 ft. 2. 0 ft. 3. (
\	TATIC WATER LEVEL 209 ft. below land surface measured on mo/day/yr 08/01 Pumo testdata: Well water was 381 ft. after 4 hours pumping 460
: : : : : Estimated	d Yield 400 gpm: Well water was 0 ft. after 0 hours oumping (
	e Diameter 24 in. to 428 ft and in. to 0 ft.
: WELL WATE	ER TO BE USED AS: 02 IRRIGATION
Was a che	emical/bacteriological sample submitted to department? No :
TYPE OF BLANK CASING USED: 01 STEEL Blank casing diameter 16 in. to 428 ft Casing height above land surface 12 in TYPE OF SCREEN OR PERFORATION MATERIAL: 01 STEEL	t., Dia in. to 0 ft., Dia in. to 0 ft. weight 42 lbs/ft. Wall thickness or gauge No 250 L
TYPE OF BLANK CASING USED: 01 STEEL Blank casing diameter 16 in. to 428 ft Casing height above land surface 12 in TYPE OF SCREEN OR PERFORATION MATERIAL: 01 STEEL SCREEN OR PERFORATION OPENINGS ARE: 01 CONT. SCREEN PERFORATED INTERVALS: From 280 From 378	CASING JOINTS: WELDED t., Dia in. to 0 ft., Dia in. to 0 ft. weight 42 lbs/ft. Wall thickness or gauge No250 L SLOT Oft. to 360 ft From 0 ft. to 0 ft. 5 ft. to 425 ft From 0 ft. to 0 ft.
TYPE OF BLANK CASING USED: 01 STEEL Blank casing diameter 16 in. to 428 ft Casing height above land surface 12 in TYPE OF SCREEN OR PERFORATION MATERIAL: 01 STEEL SCREEN OR PERFORATION OPENINGS ARE: 01 CONT. SCREEN PERFORATED INTERVALS: From 280 From 375 GRAVEL PACK INTERVALS: From 20	CASING JOINTS: WELDED t., Dia in. to 0 ft., Dia in. to 0 ft. weight 42 lbs/ft. Wall thickness or gauge No250 L SLOT Oft. to 360 ft From 0 ft. to 0 ft.
TYPE OF BLANK CASING USED: 01 STEEL Blank casing diameter 16 in. to 428 ft Casing height above land surface 12 in TYPE OF SCREEN OR PERFORATION MATERIAL: 01 STEEL SCREEN OR PERFORATION OPENINGS ARE: 01 CONT. SCREEN PERFORATED INTERVALS: From 280 From 378 GRAVEL PACK INTERVALS: From 20 From 0	CASING JOINTS: WELDED t., Dia in. to 0 ft., Dia in. to 0 ft. weight 42 lbs/ft. Wall thickness or gauge No250 L SLOT Oft. to 360 ft From 0 ft. to 0 ft. 5 ft. to 425 ft From 0 ft. to 0 ft. Oft. to 428 ft From 0 ft. to 0 ft. Oft. to 0 ft From 0 ft. to 0 ft. From 0 ft. to 0 ft From 0 ft. to 0 ft. NONE OBSERVED
TYPE OF BLANK CASING USED: 01 STEEL Blank casing diameter 16 in. to 428 ft Casing height above land surface 12 in TYPE OF SCREEN OR PERFORATION MATERIAL: 01 STEEL SCREEN OR PERFORATION OPENINGS ARE: 01 CONT. SCREEN PERFORATED INTERVALS: From 280 From 375 GRAVEL FACK INTERVALS: From 20 From 0 GROUT MATERIAL 03 BENTONITE Grout Intervals: From 0 ft. to 20 ft What is the nearest source of possible contamina Direction from well?	CASING JOINTS: WELDED t., Dia in. to 0 ft., Dia in. to 0 ft. weight 42 lbs/ft. Wall thickness or gauge No250 L SLOT Oft. to 360 ft From 0 ft. to 0 ft. 5 ft. to 425 ft From 0 ft. to 0 ft. Oft. to 428 ft From 0 ft. to 0 ft. Oft. to 0 ft From 0 ft. to 0 ft. From 0 ft. to 0 ft From 0 ft. to 0 ft. How many feet?
TYPE OF BLANK CASING USED: 01 STEEL Blank casing diameter 16 in. to 428 ft Casing height above land surface 12 in TYPE OF SCREEN OR PERFORATION MATERIAL: 01 STEEL SCREEN OR PERFORATION OPENINGS ARE: 01 CONT. SCREEN PERFORATED INTERVALS: From 280 From 378 GRAVEL PACK INTERVALS: From 20 From 0 GROUT MATERIAL 03 BENTONITE Grout Intervals: From 0 ft. to 20 ft What is the nearest source of possible contaminal Direction from well? FROM TO LITHOLOGIC LC	CASING JOINTS: WELDED t., Dia in. to 0 ft., Dia in. to 0 ft. weight 42 lbs/ft. Wall thickness or gauge No250 L SLOT Oft. to 360 ft From 0 ft. to 0 ft. 5 ft. to 425 ft From 0 ft. to 0 ft. Oft. to 428 ft From 0 ft. to 0 ft. Oft. to 0 ft From 0 ft. to 0 ft. From 0 ft. to 0 ft From 0 ft. to 0 ft. How many feet?
TYPE OF BLANK CASING USED: 01 STEEL Blank casing diameter 16 in. to 428 ft Casing height above land surface 12 in TYPE OF SCREEN OR PERFORATION MATERIAL: 01 STEEL SCREEN OR PERFORATION OPENINGS ARE: 01 CONT. SCREEN PERFORATED INTERVALS: From 280 From 378 GRAVEL PACK INTERVALS: From 20 From 0 GROUT MATERIAL 03 BENTONITE Grout Intervals: From 0 ft. to 20 ft What is the nearest source of possible contaminal Direction from well? FROM 1	CASING JOINTS: WELDED t., Dia in. to 0 ft., Dia in. to 0 ft. weight 42 lbs/ft. Wall thickness or gauge No250 L SLOT Oft. to 360 ft From 0 ft. to 0 ft. 5 ft. to 425 ft From 0 ft. to 0 ft. Oft. to 428 ft From 0 ft. to 0 ft. Oft. to 0 ft From 0 ft. to 0 ft. From 0 ft. to 0 ft From 0 ft. to 0 ft. How many feet?
TYPE OF BLANK CASING USED: 01 STEEL Blank casing diameter 16 in. to 428 ft Casing height above land surface 12 in TYPE OF SCREEN OR PERFORATION MATERIAL: 01 STEEL SCREEN OR PERFORATION OPENINGS ARE: 01 CONT. SCREEN PERFORATED INTERVALS: From 280 From 375 GRAVEL PACK INTERVALS: From 20 From 0 GROUT MATERIAL 03 BENTONITE Grout Intervals: From 0 ft. to 20 ft What is the nearest source of possible contaminal Direction from well? FROM 1	CASING JOINTS: WELDED t., Dia in. to 0 ft., Dia in. to 0 ft. weight 42 lbs/ft. Wall thickness or gauge No250 L SLOT Oft. to 360 ft From 0 ft. to 0 ft. 5 ft. to 425 ft From 0 ft. to 0 ft. Oft. to 428 ft From 0 ft. to 0 ft. Oft. to 0 ft From 0 ft. to 0 ft. From 0 ft. to 0 ft From 0 ft. to 0 ft. How many feet?
TYPE OF BLANK CASING USED: 01 STEEL Blank casing diameter 16 in. to 428 ft Casing height above land surface 12 in TYPE OF SCREEN OR PERFORATION MATERIAL: 01 STEEL SCREEN OR PERFORATION OPENINGS ARE: 01 CONT. SCREEN PERFORATED INTERVALS: From 280 From 378 GRAVEL PACK INTERVALS: From 20 From 0 GROUT MATERIAL 03 BENTONITE Grout Intervals: From 0 ft. to 20 ft What is the nearest source of possible contamination of the conta	CASING JOINTS: WELDED t., Dia in. to 0 ft., Dia in. to 0 ft. weight 42 lbs/ft. Wall thickness or gauge No250 L . SLOT Oft. to 360 ft From 0 ft. to 0 ft. 5 ft. to 425 ft From 0 ft. to 0 ft. Oft. to 428 ft From 0 ft. to 0 ft. Oft. to 0 ft From 0 ft. to 0 ft. From 0 ft. to 0 ft From 0 ft. to 0 ft. Ation: NONE OBSERVED How many feet?
TYPE OF BLANK CASING USED: 01 STEEL Blank casing diameter 16 in. to 428 ft Casing height above land surface 12 in TYPE OF SCREEN OR PERFORATION MATERIAL: 01 STEEL SCREEN OR PERFORATION OPENINGS ARE: 01 CONT. SCREEN PERFORATED INTERVALS: From 280 From 375 GRAVEL PACK INTERVALS: From 20 From 0 GROUT MATERIAL 03 BENTONITE Grout Intervals: From 0 ft. to 20 ft What is the nearest source of possible contamina Direction from well? FROM : TO : LITHOLOGIC LC 0 : 2 : 02 SILT 2 : 10 : 03 SILTY CLAY 07 FINE SAND 10 : 20 : 03 SILTY CLAY 20 : 43 : 01 CLAY 43 : 63 : 07 FINE SAND 08 MEDIUM SAND 63 : 75 : 04 SANDY CLAY 05 SAND	CASING JOINTS: WELDED t., Dia in. to 0 ft., Dia in. to 0 ft. weight 42 lbs/ft. Wall thickness or gauge No250 L . SLOT Oft. to 360 ft From 0 ft. to 0 ft. 5 ft. to 425 ft From 0 ft. to 0 ft. Oft. to 428 ft From 0 ft. to 0 ft. Oft. to 0 ft From 0 ft. to 0 ft. From 0 ft. to 0 ft From 0 ft. to 0 ft. Ation: NONE OBSERVED How many feet?
TYPE OF BLANK CASING USED: 01 STEEL Blank casing diameter 16 in. to 428 ft Casing height above land surface 12 in TYPE OF SCREEN OR PERFORATION MATERIAL: 01 STEEL SCREEN OR PERFORATION OPENINGS ARE: 01 CONT. SCREEN PERFORATED INTERVALS: From 26 From 378 GRAVEL PACK INTERVALS: From 20 From 0 GROUT MATERIAL 03 BENTONITE Grout Intervals: From 0 ft. to 20 ft What is the nearest source of possible contamination of the diameter of the contamination of the contamina	CASING JOINTS: WELDED t., Dia in. to 0 ft., Dia in. to 0 ft. weight 42 lbs/ft. Wall thickness or gauge No250 L . SLOT Oft. to 360 ft From 0 ft. to 0 ft. 5 ft. to 425 ft From 0 ft. to 0 ft. Oft. to 428 ft From 0 ft. to 0 ft. Oft. to 0 ft From 0 ft. to 0 ft. From 0 ft. to 0 ft From 0 ft. to 0 ft. Ation: NONE OBSERVED How many feet?
TYPE OF BLANK CASING USED: 01 STEEL Blank casing diameter 16 in. to 428 ft Casing height above land surface 12 in TYPE OF SCREEN OR PERFORATION MATERIAL: 01 STEEL SCREEN OR PERFORATION OPENINGS ARE: 01 CONT. SCREEN PERFORATED INTERVALS: From 280 From 375 GRAVEL PACK INTERVALS: From 20 From 0 GROUT MATERIAL 03 BENTONITE Grout Intervals: From 0 ft. to 20 ft What is the nearest source of possible contamina Direction from well? FROM : TO : LITHOLOGIC LC 0 : 2 : 02 SILT 2 : 10 : 03 SILTY CLAY 07 FINE SAND 10 : 20 : 03 SILTY CLAY 20 : 43 : 01 CLAY 43 : 63 : 07 FINE SAND 08 MEDIUM SAND 63 : 75 : 04 SANDY CLAY 05 SAND	CASING JOINTS: WELDED t., Dia in. to 0 ft., Dia in. to 0 ft. weight 42 lbs/ft. Wall thickness or gauge No250 L . SLOT Oft. to 360 ft From 0 ft. to 0 ft. 5 ft. to 425 ft From 0 ft. to 0 ft. Oft. to 428 ft From 0 ft. to 0 ft. Oft. to 0 ft From 0 ft. to 0 ft. From 0 ft. to 0 ft From 0 ft. to 0 ft. Ation: NONE OBSERVED How many feet?

! Water Well Contractor's License No. 145 This Water Well Record was completed on (mo/day/yr) 08/20/97

under the business name of **HENKLE DRILLING & SUPPLY**

WATER WELL RECORD Form WWC-5 KSA 82a-1212

OCATION DUNTY:	N OF WATER O95 STEV	WELL:	1 01 ·	1 T 33 S 1 R 39 W	
		LESTER, BEVERLY			
R#, 5t.	. Address,	Box # : 1200 S ADAMS	Board of Ag	riculture, Division of Water Resources	
City, State, ZIP code : HUGOTON, KS 67951-			Application Number: 42,515		
	; TD		!		
		20 LIMESTONE	1		
		: 04 SANDY CLAY 20 LIMESTONE	T r		
134	160	: 04 SANDY CLAY 05 SAND 20 LIMESTONE	t ;		
		: 01 CLAY	1 1		
		: 01 CLAY	1		
		05 SAND 11 GRAVEL	1		
		05 SAND 28 RDCK	1		
		: 04 SANDY CLAY	:		
		OS SAND OI CLAY	:		
		05 SAND 28 ROCK 01 CLAY 01 CLAY 31 CALICHE 20 LIMESTONE	1		
375		OI CLAY OF VERY FN SAND			
393		O1 CLAY O6 VERY FN SAND O1 CLAY	: !		
425		OI CLAY	1		
		01 CLAY 06 VERY FN SAND	•		
		O1 CLAY O7 FINE SAND	1		
482		19 SHALE 01 CLAY	1		
	! !	1 1	1		
!	! ;	1	!		
!	t I	!!	<u> </u>		
	<u>:</u>	1	1		
	1		!		
	:	1 !			
:	:	: : :	1		
	; t	i t			
	;	f 1	1		
	! !	•	1		
	* *	· !	1		
	!	· !	3 1		
	! }	• •	‡ ?		
	t ,	1 i	! !		
	1 1	¥	\$ 5		
	I I	1	‡ ‡		
	1	1	•		
	: :	: 1	* *		
	i 1	:	1		
	1	; {	•		
	1	1	‡ 1		
	1	1	1		
	1	; !	1		
	t	•	f		

17 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was tompleted on (mo/day/year) 07/29/97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 145

This Water Well Record was completed on (mo/day/yr) 08/20/97

under the business name of HENKLE DRILLING & SUPPLY

by (signature)