

1 LOCATION OF WATER WELL: County: Stevens	Fraction C $\frac{1}{4}$ NE $\frac{1}{4}$ SE $\frac{1}{4}$	Section Number 36	Township Number T 33 S	Range Number R 39 EW
---	---	-----------------------------	----------------------------------	--------------------------------

Distance and direction from nearest town or city street address of well if located within city?

Feterita: 1 West approximately 1 South West into

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :	EOG Resources Inc 3817 NW Expressway Ste 500 Oklahoma City, Ok 73112-1483	Bane 36-1 Board of Agriculture, Division of Water Resources Application Number: 20060083
---	---	---

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 400 ft. ELEVATION: 130
	Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 130 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield 100 gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Domestic (lawn & garden) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	3 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	9 Other (specify below)	Welded
2 PVC	4 ABS	7 Fiberglass	Threaded
Blank casing diameter 6 in. to 340 ft., Dia 4 in. to 0.74 ft., Dia 21.316 ft.			
Casing height above land surface 2 in., weight 4 lbs./ft. Wall thickness or guage No. SDR 21.316			
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 Fiberglass	7 PVC	10 Asbestos-Cement
1 Steel	3 Stainless Steel	8 RMP (SR)	11 Other (Specify)
2 Brass	4 Galvanized Steel	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	5 Guazed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 340 ft. to 400 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 140 ft. to 400 ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other hole plug
Grout Intervals: From 1 ft. to 25 ft., From ft. to ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	14 Abandoned water well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	15 Oil well/Gas well
Direction from well? South			13 Insecticide storage	16 Other (specify below)
			How many feet? 250	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	8	Sandy topsoil			
8	37	Sandy clay			
37	68	Sand			
68	110	Sandy clay and clay			
110	155	Sandy clay			
155	172	Sand			
172	214	Clay			
214	238	Sand			
238	317	Clay and sandy clay			
317	336	Clay			
336	397	Sand			
397	405	Tan and pink clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-6-06 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No KWWCL 430 This Water Well Record was completed on (mo/day/yr) 3-6-06 under the business name of Howard Drilling CO Box 806 Beaver Ok 73932 by (signature) <i>Thi's Hammond</i>
--