		M-111	WATER V	VELL RECORD	Form W	VC-5 KSA	82a-1212			
		TER WELL:	Fraction			Section Numl		hip Number	Range Number	
	Morton		NE 1/4		SW 1/4	4	Ìт	33 s	R 39 E/W	
Distance	and direction	from nearest town	or city street addre	ess of well if loca	ted within c	ity?				
5½ North of Rolla 3½ East										
		VNER: Ron De								
		× # : Rolla		1			Door	d of Amileude	Divinion of Minter Design	
	e, ZIP Code		, ND 0755-						Division of Water Resources	
2 LOCAT	E MELLIC I	OCATION WITH			160		Appli	cation Number:		
3 LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL. 160 ft. ELEVATION:										
N Depth(s) Groundwater Encountered 1ft, 2										
<b> </b>	WELL'S STATIC WATER LEVEL 100 ft. below land surface measured on mo/day/yr									
	Pump test data: Well water was 105 ft. after 2 hours pumping .30 gpn									
il l	Est. Yield									
<u>.</u>	Bore Hole Diameter. 9									
Į≅ W I										
l <del>-</del>	The series of th								Or (O)	
[] <b>i</b>	1 2M1 2F 1								Other (Specify below)	
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well									
<u>                                     </u>				eriological sample	submitted					
			itted				Water Well Disir			
5 TYPE	OF BLANK	CASING USED:	5	Wrought iron	8 Cd	oncrete tile	CASING	G JOINTS: Glued	d 💥 Clamped	
1 St	teel	3 RMP (SR)	6	Asbestos-Cement	t 9 Ot	her (specify be	elow)	Weld	ed .'	
2 P	VC	4 ABS	7	Fiberglass				. Threa	aded	
2 PVC       4 ABS       7 Fiberglass       Threaded.         Blank casing diameter       5       in. to       120       ft., Dia       in. to       ft.										
Casing height above land surface. 14 in., weight 200 lbs./ft. Wall thickness or gauge No. 0-265										
TYPE OF SCREEN OR PERFORATION MATERIAL:										
1 St		3 Stainless st		Fiberglass			· -		1	
2 Br		4 Galvanized		Concrete tile		RMP (SR)				
			<del>-</del>		-	ABS		None used (op	<i>'</i>	
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)										
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes										
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)										
OSTREET ET STATES INTERIORES.   TIOIT										
From										
GRAVEL PACK INTERVALS: From. 95 ft. to 160 ft., From ft. to										
From ft. to ft., From ft. to ft										
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Rentonite 4 Other										
Grout Intervals: From										
What is th	ne nearest so	ource of possible cor	ntamination:	,,		10 Lis	estack name		bandoned water well	
1 Septic tank 4 Lateral lin						10 Livestock pens				
•								15 Oil well/Gas well		
									ther (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? None Pasture Well How many feet?										
	from well?	r · · · · · · · · · · · · · · · · · · ·					many feet?			
FROM	100		LITHOLOGIC LOC	<u> </u>	FROM	и то		PLUGGING II	NTERVALS	
0	100	Overburde								
_100_	120	Medium sa								
120	140	Medium sa	nd and cla	ay						
140	160	Medium sa	nd and cla	ч		-				
							<b>_</b>			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed. (2) reconstructed, or (3) plugged under my jurisdiction and was										
completed on (mo/day/year)										
completed on (mo/day/year)										
			+酒 <b>か</b>	inis Water V	vell Hecord				<i>1111</i>	
	business na		Water Wel					. Wagen	zellu-	
INSTRU of Heal	JCTIONS: Use to the and Environm	ypewriter or ball point pen. ent, Bureau of Water, Top	PLEASE PRESS FIRML eka, Kansas 66620-7320	<u>Y</u> and <u>PRINT</u> clearly. F D. Telephone: 913-296-	Please fill in bla 5545. Send on	nks, underline or c to WATER WELL	ircle the correct answ . OWNER and retain	ers. Send for three of one for your records	opies to Kansas Department	