

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: MORTON		SE 1/4 SE 1/4 NE 1/4	32	T 33S S	R 39W E/W
Distance and direction from nearest town or city street address of well if located within city?					
2 WATER WELL OWNER: MINTER - WILSON DRILLING CO.					
RR#, St. Address, Box #		W - HIWAY 50		Board of Agriculture, Division of Water Resources	
City, State, ZIP Code		GARDEN CITY, KS 67846		Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 330 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 80 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 80 ft. below land surface measured on mo/day/yr 11-15-93			
		Pump test data: Well water was 100 ft. after 1 hours pumping 50 gpm			
		Est. Yield 50 gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 11 in. to 330 ft. and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)		5 Wrought iron	
2 PVC		4 ABS		6 Asbestos-Cement	
				7 Fiberglass	
Blank casing diameter 6 in. to 340 ft. Dia				9 Other (specify below)	
Casing height above land surface 24 in., weight 2.902 lbs./ft. Wall thickness or gauge No. 280 SDR 21				CASING JOINTS: Glued X Clamped	
TYPE OF SCREEN OR PERFORATION MATERIAL:				Welded	
1 Steel		3 Stainless steel		7 PVC	
2 Brass		4 Galvanized steel		8 RMP (SR)	
				9 ABS	
SCREEN OR PERFORATION OPENINGS ARE:				10 Asbestos-cement	
1 Continuous slot		3 Mill slot		11 Other (specify)	
2 Louvered shutter		4 Key punched		12 None used (open hole)	
				8 Saw cut	
				9 Drilled holes	
				10 Other (specify)	
SCREEN-PERFORATED INTERVALS:		From 270 ft. to 340 ft.		11 None (open hole)	
		From ft. to ft.			
GRAVEL PACK INTERVALS:		From 260 ft. to 340 ft.			
		From ft. to ft.			
6 GROUT MATERIAL:					
1 Neat cement		2 Cement grout		3 Bentonite	
4 Other		HOLE PLUG			
Grout intervals: From 1 ft. to 20 ft.		From ft. to ft.		From ft. to ft.	
What is the nearest source of possible contamination:				10 Livestock pens	
1 Septic tank		4 Lateral lines		14 Abandoned water well	
2 Sewer lines		5 Cess pool		11 Fuel storage	
3 Watertight sewer lines		6 Seepage pit		15 Oil well/Gas well	
				12 Fertilizer storage	
				16 Other (specify below)	
				13 Insecticide storage	
Direction from well?				How many feet?	
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS			
0 10 TOP SOIL					
10 95 FINE TO COARSE SAND GRAVEL FROM 60-95					
95 100 CALICHE					
100 160 SANDY CLAY					
160 185 SANDY RED CLAY					
185 198 FINE SAND					
198 295 SANDY CLAY					
295 315 FINE SAND					
315 340 SANDY RED & BLUE CLAY & STREAKS OF RED BED.					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-15-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. KWWCL-430 This Water Well Record was completed on (mo/day/yr) 11-15-93 under the business name of HOWARD DRLG.CO.BOX 806 BEAVER, OK 73932 by (signature)					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					