


1 LOCATION OF WATER WELL: County: Stevens	Fraction NW 1/4 SE 1/4 SE 1/4	Section Number 15	Township Number T 33 S	Range Number R 39 E/W
--	----------------------------------	----------------------	---------------------------	--------------------------

Distance and direction from nearest town or city street address of well if located within city?

11 West 3/4 South of Hugoton, KS

2 WATER WELL OWNER: Texaco A	Gabbert & Jones
RR#, St. Address, Box # :	333 E. English Suite 215
City, State, ZIP Code :	Wichita, KS 67202
	Board of Agriculture, Division of Water Resources
	Application Number: T 88-411

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 380 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 220 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 160 ft. below land surface measured on mo/day/yr 8-17-88
	Pump test data: Well water was 140 ft. after 2 hours pumping 55 gpm
	Est. Yield 60 gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 9 in. to 380 ft., and in. to ft.
	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
	Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Threaded
Blank casing diameter 5 in. to 0-280 ft., Dia			
Casing height above land surface 14 in., weight 200 lbs./ft.			Wall thickness or gauge No. 0.265
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 280 ft. to 380 ft.			
GRAVEL PACK INTERVALS: From 150 ft. to 380 ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 20 ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? Southwest			How many feet? 200	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	160	Overburden			
160	180	Clay and medium sand streaks			
180	200	Clay and medium sand streaks			
200	220	Clay			
220	240	Clay			
240	260	Clay			
260	280	Clay			
280	300	Clay			
300	310	Clay			
310	360	Medium sand and clay			
360	380	Redbed			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-17-88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 142 This Water Well Record was completed on (mo/day/yr) 8-26-88 under the business name of T & W WATER WELL SERVICE, INC. by (signature) D. Wagenseller
