			WELL RECORD	Form WWC-5	KSA 82a			
LOCATION OF WA		Fraction			on Number	Township Nur		Range Number
County: Steve	ns	NE⁄4	SE ¼ N		36	т 33	s	R 39 E/W
		•	dress of well if located	•				
2 West of	<u>Federita,</u>	KS 1 3/4	South East	into				
WATER WELL OV	/NER: #H-1	Nix	Gabbert					
RR#, St. Address, Bo	<b>x #</b> :		333 E.	English		Board of Agriculture, Division of Water Resources		
city, State, ZIP Code	Wichita	, KS 672	02	Application Number: 900228				
LOCATE WELL'S L	OCATION WITH	4 DEPTH OF CO	MPLETED WELL	240	. ft. ELEVA	TION:		
AN "X" IN SECTIO	N BOX:	Depth(s) Groundw	ater Encountered 1	130	ft. 2		ft. 3	
ī .	1	WELL'S STATIC	WATER LEVEL	1.10 ft. be	low land sur	ace measured on	mo/day/yr .6	-4-90
		Pump	test data: Well water	r was 105	ft. a	ter	hours pumpi	ng <b>7.0</b> gpm
NW	NE	Est. Yield 7.0	gpm: Well wate	r was	ft. at	ter	hours pumpi	ng gpm
<u>.</u>   ;	i  .	Bore Hole Diamet	er <b>9</b> in. to	240		and	in. to	
w	1	WELL WATER TO	D BE USED AS:	5 Public water	supply	8 Air conditioning	11 Inje	ction well
-   1		1 Domestic	3 Feedlot	6 Oil field water	er supply	9 Dewatering	12 Oth	er (Specify below)
sw	56	2 Irrigation	4 Industrial	7 Lawn and ga	arden only	0 Monitoring well	,	
i		Was a chemical/ba	acteriological sample s	submitted to De	partment? Ye	sNo <b>X</b>	; If yes, mo	/day/yr sample was sub
	\$	mitted			Wa	ter Well Disinfected	? Yes X	No
TYPE OF BLANK	CASING USED:		5 Wrought iron	8 Concre	te tile	CASING JOIN	ITS: Glued .X	Clamped
1 Steel	3 RMP (S	SR)	6 Asbestos-Cement	9 Other (	specify below	<i>(</i> )	Welded .	
2 PVC	4 ABS		7 Fiberglass					<b>3</b> <i></i>
Blank casing diameter	· , , , , , , <u>5</u> , , , , ,	.in. to 140	ft., Dia	in. to		ft., Dia	in.	to ft.
Casing height above	and surface	<b>1.4</b> i	in., weight	200	Ibs./	ft. Wall thickness o	r gauge No.	0.265
TYPE OF SCREEN C	R PERFORATIO	N MATERIAL:		_7_PV0		10 Asbe	stos-cement	
1 Steel	3 Stainles	s steel	5 Fiberglass	8 RMI	P (SR)	11 Othe	r (specify)	
2 Brass	4 Galvania	zed steel	6 Concrete tile	9 ABS	3	12 None	used (open	hole)
SCREEN OR PERFO	RATION OPENIN	NGS ARE:	5 Gauz	ed wrapped		8 Saw cut	11	None (open hole)
1 Continuous sl	ot 3 M	Mill slot	6 Wire	wrapped		9 Drilled holes		
2 Louvered shu	ter 4 K	Key punched	7 Torch	cut		10 Other (specify)		
SCREEN-PERFORAT	ED INTERVALS:	From1	40 ft. to	240	ft., Fro	n	ft. to	
		From	ft. to	<u>.</u>	ft., Fro	n <i>.</i>	ft. to	
GRAVEL PA	CK INTERVALS	: From1	00 ft. to	240	ft., Fro	m	ft. to	
		From	ft. to		ft., Froi	m	ft. to	ft.
GROUT MATERIA			2 Cement grout					
Grout Intervals: Fro	<sub>m</sub> O	.ft. to 20	ft., From	ft. t	0			ft. to
What is the nearest s	ource of possible	contamination:			10 Lives	tock pens		doned water well
1 Septic tank 4 Lateral lines			7 Pit privy		11 Fuel storage			
2 Sewer lines 5 Cess pool			8 Sewage lagoon		12 Fertilizer storage 16 Other (specify bel		r (specify below)	
3 Watertight set	ver lines 6 Seep		9 Feedyard		13 Insec	ticide storage		
Direction from well?	South				How ma	19 1001.	50	
FROM TO		LITHOLOGIC L	_OG	FROM	ТО	PLI	JGGING INTI	ERVALS
0 110	Overbur	den						
110   130	Fine sar	nd and cla	у					
130   160	Fine sar	nd and cla	у					
160   180		sand and c		<b>_</b>				
180 200	Medium	sand and c	lay					
200 220	Fine sa	nd and cla	<b>y</b>					
220 240	Fine sa	nd and cla	<b>y</b>					
								and a second residence of the second
							at	
	ļ							
CONTRACTOR'S	OR LANDOWNE	R'S CERTIFICATION	ON: This water well u	as (1) constru	ted (2) reco	enstructed or (3) o	luaged under	my jurisdiction and was
completed on (mo/day		4-90						ledge and belief. Kansa
Water Well Contracto		142	This Water V				6-18-90	
TAKEL TYEN CONTRACTO	S LICE!ISE INC.		IIIIS VValer V	TOIL FIECUIU WA	o completed	OTT (THO/COPPE/VI)	<del>-</del> <b>-</b> . <b>-</b>	/2
inder the husiness a	ame of The	& W Water		e. Inc	by (eigns	ture) CV 1/1	100	100
inder the business n			Well Servic				and too three con	Cle