

1 LOCATION OF WATER WELL: Fraction SW 1/4 SE 1/4 SW 1/4 Section Number 9 Township Number T 33 S Range Number R 40 W E W

Distance and direction from nearest town or city street address of well if located within city?
5 NW of Rolla, KS

2 WATER WELL OWNER: ANADARKO PETROLEUM CORP. #I-2 LOW
RR#, St. Address, Box #: HCR 2, BOX 25 Board of Agriculture, Division of Water Resources
City, State, ZIP Code: STINNETT, TEXAS 79083 Application Number: 940387

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 2x2 grid with NW, NE, SW, SE quadrants. An 'X' is marked in the SW quadrant. A vertical scale on the left indicates 1 Mile.]

4 DEPTH OF COMPLETED WELL: 320 ft. ELEVATION: 40 ft.
Depth(s) Groundwater Encountered 1. 40 ft. 2. ft. 3. ft.
WELL'S STATIC WATER LEVEL: 40 ft. below land surface measured on mo/day/yr 9-28-94
Pump test data: Well water was 60 ft. after 1 hours pumping 100 gpm
Est. Yield 100 gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter: 9 1/2 in. to 320 ft., and in. to ft.
WELL WATER TO BE USED AS:
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
7 Fiberglass Threaded
Blank casing diameter 5 in. to 340 ft. Dia in. to ft. Dia in. to ft.
Casing height above land surface 24 in. weight 2.902 lbs./ft. Wall thickness or gauge No. 265 SDR 21
TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
7 Torch cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 220 ft. to 320 ft. From ft. to ft.
GRAVEL PACK INTERVALS: From 200 ft. to 320 ft. From ft. to ft.
From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 1 Heat cement 2 Cement grout 3 Bentonite 4 Other HOLE PLUG
Grout Intervals: From 1 ft. to 20 ft. From ft. to ft. From ft. to ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage
Direction from well? West How many feet? 100

LITHOLOGIC LOG			PLUGGING INTERVALS		
FROM	TO		FROM	TO	
0	2	BLOW SAND	286	309	SAND STONE
2	10	SAND	309	320	RED
10	19	LARGE GRAVEL			
19	45	SAND			
45	53	CLAY			
53	61	GRAVEL & SANDY CLAY			
61	74	SANDY CLAY			
74	82	CLAY			
82	129	SANDY CLAY			
129	156	CLAY			
156	181	SANDY CLAY			
181	203	CLAY			
203	233	SAND			
233	249	CLAY			
249	286	FINE SAND & SAND STONE			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-28-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. KWWCL-430 This Water Well Record was completed on (mo/day/yr) 9-28-94 under the business name of HOWARD DRUG CO. BOX 806 BEAVER, OK 73932 by (signature) Howard

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T
R
EW
SEC.