WATER WELL RECORD Form WWC-5	Division of Water Resources App. No.
1 LOCATION OF WATER WELL: Fraction	Section Number Township No. Range Number
County: Morton NE 1/4 1/4 1/4 1/4	1 00 0 1 1 10 10 10
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here	Global Positioning System (GPS) information: Latitude:N37,182199
195 County Road P	Longitude: W102.026361 (in decimal degrees)
Richfield, Kansas	Elevation:
2 WATER WELL OWNER: Colorado Interstate Gas Company	Datum: WGS 84, NAD 83, NAD 27
RR#, Street Address, Box #: 2060 N. Briargate	Collection Method: GPS unit (Make/Model: Handy GPS)
City, State, ZIP Code : Colorado Springs, CO 80920	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey
3 LOCATE WELL	Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☑ 5-15 m, ☐ >15 m
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 135	ft. Mc-NW-11
SECTION BOX: Depth(s) Groundwater Encountered (1)	ft. (2) ft. (3) ft.
N WELL'S STATIC WATER LEVELft.	below land surface measured on mo/day/yr
I DOT MEID WILL A	ft. after hours pumping gpmft. after hours pumping gpm
WNW NE EST. YIELDgpm. Well water was	t. and in to
	er supply Geothermal Injection well
SWSE Domestic Feedlot Oil field water	r supply Dewatering Other (Specify below)
	/n & garden ☑ Monitoring well
Was a chemical/bacteriological sample submitted to If yes, mo/day/yr sample was submitted	
mile Water well disinfected?	
5 TYPE OF CASING USED: Steel V PVC Other	
CASING JOINTS: Glued Clamped Welded Threaded	
Casing diameter 2 in. to .135 ft., Diameter in. to ft., Diameter in. to ft.	
Casing height above land surface36	
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)	
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:	
☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole) ☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☐ Saw cut ☐ Other (specify)	
SCREEN-PERFORATED INTERVALS: From 105 ft. to 135 ft., From ft. to ft.	
From	
GRAVEL PACK INTERVALS: From. ft. to 138 ft., From ft. to ft. From. ft. to ft., From ft. to ft.	
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other	
Grout Intervals: From .98 ft. to .103 ft., From ft. to ft., From ft. to ft.	
What is the nearest source of possible contamination:	<u> </u>
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock p ☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☑ Fuel storage	
Watertight sewer lines Seepage pit Feedyard Fertilizer sto	
Direction from well	rom well
FROM TO LITHOLOGIC LOG FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVALS
0 4 Reddish Brown Silt 4 52 Brown Sand	
52 65 Brown Silt	
65 89 Yellowish Brown Clay	
89 140 Brownish Clay	
140 150 Brown Clay	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged	
under my jurisdiction and was completed on (mo/day/year) .2/21/12 and this record is true to the best of my knowledge and belief.	
Kansas Water Well Contractor's License No763 This Water Well Record was completed on (mo/day/year) .03/30/12	
under the business name of Peterson Drilling and Testing, Inc by (signature) by (signature) INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies	
(white, blue, pink) to Kansas Depar tment of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Toneka, Kansas 66612-1367	
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include <u>fee</u> of \$5.00 for each constructed well. Vi sit us at http://www.kdheks.gov/waterwell/index.html .	
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy	