WATER WELL RECORD		Form W	WC-5	Division of Water Resources App. No.		
1 LOCATION OF WATER WELL:		Fraction	)	Section Number	Township No.	Range Number
		E/2 1/Sh			т 33 s	R 6 □E XW
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here						
from nearest town or		Latitude: (in decimal degrees)				
HWY 44 : SE 40 Ave				Longitude: (in decimal degrees)		
486 E St. RJ. 44, Anthony, KS 67003				Elevation:		
2 WATER WELL OWNER: Jeff Duncan				Collection Method:		
RR#, Street Address, Box #:				GPS unit (Make/Model:)		
City, State, ZIP Code :				☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey		
<u>Est. Accuracy</u> : ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m						
3 LOCATE WELL	A DEPTH OF	COMPLETED WEI		ho .		
WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 70 ft.  Depth(s) Groundwater Encountered (1) ft. (2) ft. (3) ft.					
SECTION BOX:	WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr					
Pump test data: Well water wasft. after hours pumping						
l l nom turne V						
W   Bore Hole Diameter						
WELL WATER TO BE USED AS: ☐ Public water supply ☐ Geothermal ☐ Injection well						
SW SE Domestic  Feedlot  Oil field water supply  Dewatering  Other (Specify below)						
Irrigation Industrial Domestic-lawn & garden Monitoring well						
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No						
S If yes, mo/day/yr sample was submitted						
Water well disinfected?     Yes □ No						
5 TYPE OF CASING USED: Steel PVC Other						
CASING JOINTS:  Glued  Clamped  Welded  Threaded						
Casing diameter						
Casing height above land surfacein., Weightlbs./ft., Wall thickness or gauge NoSDR-26						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)						
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE:						
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)						
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From ft. to ft. ft.						
SCREEN-PERFORATED INTERVALS: From						
From						
GRAVEL PACK INTERVALS: From 12.5						
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other						
Grout Intervals: From						
What is the nearest source of possible contamination:						
Septic tank						
☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☑ Abandoned water well						
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well  Direction from well						
Direction from well			FROM	The second secon		IGGING INTERVALS
FROM TO	LITHOLOG	iic LOO	FROM	TO LITHO. LO	od (cont.) or PLL	COUNT INTERVALS
2 8 Cla	3CH	White the second was a second w				
8 14 Com	sc Clay		<del>                                     </del>			
1 100 100	1 - 1	(Ded & Come )				
	: Green Gr	who Shele			***************************************	
38 70 41	· OI VOY	3.00	<del>                                     </del>			
				/		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION; This water well was constructed, reconstructed, or plugged						
under my jurisdiction and was completed on (mo/day/year)						
Kansas Water Well Contractor's License No. 4.7.8. This Water Well Record was completed by (mo/day/year)						
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLIASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies						
(white, blue, pink) to Kansas I	WITHER OF DAIL POINT PER	and Environment Rureau	of Water Geolo	arry. Picase IIII in Dianks av Section. 1000 SW Tar	ekson St., Suite 420	Topeka, Kansas 666 12-1367
Telephone 785-296-5524. Se	ndone copy to WAT	ER WELL OWNER and	retain one for y	our records. Include fee	of \$5.00 for each co	onstructed well. Vi sit us at
http://www.kdheks.gov/waterwell/index.html.						
KSA 82a-1212				Check: Wh	nite Copy, 🔲 Bl	ue Copy, 🔲 Pink Copy