WATI	ER WE	LL RECORD	Form W	VWC-5	Γ	Division of Wate	r Resources App. No.		
		OF WATER WELL:			Sect	ion Number		Range Number	
	unty: Ha		1/4 NW 1/4 NV	N ¼ NE ½		30		R 7 DE WW	
Stre	eet/Rural	Address of Well Location;	if unknown distance	& direction					
fror	n nearest	town or intersection: If at	owner's address, chec	Lati	Global Positioning System (GPS) information: Latitude:				
1	4 1/2 miles West of Anthony on Hwy 2, South into.				Lon	Longitude:			
' '	The miles west of Anthony of Frwy 2, South into.				Elev	Elevation: (in decimal degrees)			
3 887	A CENTRAL WAY	THE T CANADA			Datu	m: WGS 84	4, □ NAD 83, □	 NAD 27	
			il - Starks-Masner	# 1	Colle	ection Method:	,		
	RR#, Street Address, Box #: 868 North US HWY 160 City, State, ZIP Code : Harner KS 67058					GPS unit (Make/Model:)			
Cit	y, State,	ZIP Code : Harper,	KS 67058			Digital Map/Ph	oto, Topographic	Map, Land Survey	
3 LO4	CATE W	RII.			Est.	Accuracy: [] <	3 m, 3-5 m, 5	5-15 m,	
	WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 35 ft.								
	ECTION BOX: Depth(s) Groundwater Encountered (1)								
	Depth(s) Groundwater Encountered (1)								
	Pump test data: Well water wasft. afterhours pumpinggp								
	EST. YIELD. 25gpm. Well water was								
w l	Bore Hole Diameter 12. 1/4 in. to .35 ft., and in. toft.								
	WELL WATER TO BE USED AS: ☐ Public water supply ☐ Geothermal ☐ Injection well								
S	SWSE ☐ Domestic ☐ Feedlot ☑ Oil field water supply ☐ Dewatering ☐ Other (Specify below)								
	Irrigation Industrial Domestic-lawn & garden Monitoring well								
<u> </u>	Was a chemical/bacteriological sample submitted to Department? Yes V No								
S If yes, mo/day/yr sample was submitted									
Water well disinfected? ✓ Yes ☐ No									
5 TYPE OF CASING USED: Steel V PVC Other									
CASING JOINTS: Glued Clamped Welded Threaded									
Casing diameter .8									
Casing neight above land surface									
1 THE OF SCREEN OR PERFORATION MATERIAL:									
☐ Steel ☐ Stainless Steel									
Brass Galvanized Steel None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
☐ Continuous slot									
Louvered shutter									
From ft to ft From ft to									
GRAVEL PACK INTERVALS: From									
From									
6 GROUT MATERIAL: Neat cement Cement grout 7 Rentonite Other									
Grout Intervals: From 14 ft. to 0 ft., From ft. to ft., From ft., Fro									
What is	the near	est source of possible conta	mination:			,	* 10111		
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)									
Sewer lines									
Dina] Watertig	ht sewer lines Seepage p	it 🗌 Feedyard	Fertilizer s	torage	Oil well/gas	s well		
Dire	ction iro	n well .East				ell300.ft		••••••	
FROM		LITHOLOG	IC LUG	FROM	ТО	LITHO. LC	OG (cont.) <u>or</u> PLUG	GING INTERVALS	
0	3	Red Shale							
3	15	Silty Sand							
8	15 30	Red Clay	With the second						
15	36	Small Sand							
30	30	Red Shale		 			nere en		
	-	The second secon							
	-	A CONTRACTOR OF THE STATE OF TH		-					
	-			 				WAS A CONTRACT OF THE CONTRACT	
	-		•				44.4		
7 CONTRACTORIS OR LANDOWNERING CERTIFICATION OF THE STATE									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged									
under my jurisdiction and was completed on (mo/day/year)!(1/1/2011 and this record is true to the best of my knowledge and belief									
Kansas Water Well Contractor's License No. 665 This Water Well Record was completed on (mo/day/year) 1/23/2012									
under the business name of Pratt Well Service by (signature) INSTRUCTIONS: Use typewriter or ball point pen PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies									
Wille, olde, pink) to Kansas Department of Health and Environment, Bureau of Water Geology Section, 1000 SW Jackson St. Suita 420, Tanala, Vanna CC 12, 1207									
rerephoni	C 703-230-	3322. Selid one copy to WAI.	ER WELL OWNER and	retain one for y	our recor	ds. Include fee	of \$5.00 for each con	structed well. Visit us at	
Intp://www.kateks.gov/waterweit/index.ntml.									
KSA 82a-1212 Check: White Copy, W Blue Copy, Pink Copy									