

1 LOCATION OF WATER WELL: County: Barber Fraction NE 1/4 NE 1/4 SE 1/4 Section Number 2 Township Number T 34 S Range Number R 12 EW

Distance and direction from nearest town or city street address of well if located within city?

3 E 7 N Hardtner

2 WATER WELL OWNER: Donald Tally RR#, St. Address, Box #: Amorita, Okla 73719 City, State, ZIP Code: Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN 'X' IN SECTION BOX: [Diagram showing a 2x2 grid with NW, NE, SW, SE quadrants and an 'X' in the SE quadrant. Includes '1 Mile' scale and 'W' 'E' labels.] 4 DEPTH OF COMPLETED WELL: 113 ft. ELEVATION: 10 ft. WELL'S STATIC WATER LEVEL: 10 ft. below land surface measured on mo/day/yr 3-15-86. Pump test data: Well water was 5 gpm after 8 hours pumping. Est. Yield 5 gpm. Well water was 8 in. after 113 ft. Bore Hole Diameter 8 in. to 113 ft. WELL WATER TO BE USED AS: 5 Public water supply, 8 Air conditioning, 11 Injection well, 1 Domestic, 3 Feedlot, 6 Oil field water supply, 9 Dewatering, 12 Other (Specify below), 2 Irrigation, 4 Industrial, 7 Lawn and garden only, 10 Observation well. Was a chemical/bacteriological sample submitted to Department? Yes No. If yes, mo/day/yr sample was submitted. Water Well Disinfected? Yes No.

5 TYPE OF BLANK CASING USED: 1 Steel, 3 RMP (SR), 2 PVC, 4 ABS, 5 Wrought iron, 6 Asbestos-Cement, 7 Fiberglass, 8 Concrete tile, 9 Other (specify below), CASING JOINTS: Glued, Clamped, Welded, Threaded. Blank casing diameter 4 in. to 9 in. Dia. Casing height above land surface 24 in., weight lbs./ft. Wall thickness or gauge No. .173.

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 3 Stainless steel, 5 Fiberglass, 8 RMP (SR), 10 Asbestos-cement, 2 Brass, 4 Galvanized steel, 6 Concrete tile, 9 ABS, 11 Other (specify), 12 None used (open hole).

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 3 Mill slot, 5 Gauzed wrapped, 8 Saw cut, 11 None (open hole), 2 Louvered shutter, 4 Key punched, 6 Wire wrapped, 9 Drilled holes, 7 Torch cut, 10 Other (specify).

SCREEN-PERFORATED INTERVALS: From 98 ft. to 113 ft. GRAVEL PACK INTERVALS: From 10 ft. to 35 ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other. Grout Intervals: From 0 ft. to 10 ft. What is the nearest source of possible contamination: 1 Septic tank, 4 Lateral lines, 7 Pit privy, 10 Livestock pens, 14 Abandoned water well, 2 Sewer lines, 5 Cess pool, 8 Sewage lagoon, 11 Fuel storage, 15 Oil well/Gas well, 3 Watertight sewer lines, 6 Seepage pit, 9 Feedyard, 12 Fertilizer storage, 16 Other (specify below), 13 Insecticide storage. Direction from well? How many feet? 50.

LITHOLOGIC LOG table with columns FROM, TO, LITHOLOGIC LOG. Entries: 0 to 10 soil, 10 to 15 silty clay, 15 to 113 red shale.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-15-86 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 140. This Water Well Record was completed on (mo/day/year) 4-10-86 under the business name of Lynn inc. by (signature) Richard Lynn.

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY T R EW SEC 1/4 1/4 1/4