

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Barber	SE $\frac{1}{4}$ SE $\frac{1}{4}$ NE $\frac{1}{4}$	29	T 34 S	R 15 EW

Distance and direction from nearest town or city street address of well if located within city?

2 miles South of Actna

2 WATER WELL OWNER:	Phillips Pipeline Co	MW 13
RR#, St. Address, Box #	12 A1 Phillips Bldg	Board of Agriculture, Division of Water Resources
City, State, ZIP Code	Barbersville OK 7004	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 25.0 ft. ELEVATION:
--	--

Depth(s) Groundwater Encountered 1. 21.0 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 19.0 ft. below land surface measured on mo/day/yr 1/30/92

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 8.14 in. to 25.0 ft. and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes.....No. X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile Casing joints: Glued Clamped

1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded

2 PVC 4 ABS 7 Fiberglass Threaded. X

Blank casing diameter 2 in. to 10.0 ft., Dia in. to in. to ft., Dia in. to ft.

Casing height above land surface 24 in., weight 0.70 lbs./ft. Wall thickness or gauge No. 5ch 40

6 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

1 Continuous slot 6 Wire wrapped 9 Drilled holes

2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 25.0 ft. to 10.0 ft., From ft. to ft. to ft.

From ft. to ft., From ft. to ft. to ft.

GRAVEL PACK INTERVALS: From 25.0 ft. to 8.0 ft., From ft. to ft. to ft.

From ft. to ft., From ft. to ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete

Grout Intervals: From 8.0 ft. to 3.0 ft., From 3.0 ft. to 0.0 ft., From 0.0 ft. to ft. to ft.

What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well

1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage

Direction from well? How many feet?

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0.0 15.5 Red Brown Sandy Lean Clay

15.5 17.0 Gray Sandy Lean Clay

17.0 25.0 Red Brown Sandy Lean Clay

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1/30/92 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 516 This Water Well Record was completed on (mo/day/yr) 1/30/92

under the business name of Geosystems Engineering Inc by (signature) 

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.