


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Sumner</u>	<u>SE 1/4 NW 1/4 NW 1/4</u>	<u>4</u>	<u>T 34 S</u>	<u>R 2 E</u> <u>(10)</u>

Distance and direction from nearest town or city street address of well if located within city?

1107 S. Robin Rd, Corbin, KS.

2 WATER WELL OWNER:	RR#, St. Address, Box #	City, State, ZIP Code	Board of Agriculture, Division of Water Resources
<u>Brent Rice</u>	<u>463 W 9th St</u>	<u>Wellington, KS 67152</u>	Application Number: <u>MW6</u>

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL	ELEVATION:
	<u>25.5</u> ft.	<u>25.5</u> ft.
Depth(s) Groundwater Encountered	1	ft. 2. ft. 3. ft.
WELL'S STATIC WATER LEVEL	<u>21.02</u> ft. below land surface measured on mo/day/yr	
Pump test data: Well water was	ft. after	hours pumping gpm
Est. Yield	gpm	Well water was ft. after hours pumping gpm
Bore Hole Diameter	<u>6.718</u> in. to <u>25.5</u> ft. and in. to ft.	
WELL WATER TO BE USED AS:	5 Public water supply	8 Air conditioning
	1 Domestic	3 Feedlot
	2 Irrigation	4 Industrial
	7 Lawn and garden only	10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes	No	X
Water Well Disinfected? Yes	No	X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued	Clamped
1 Steel <u>2</u>	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC	4 ABS	7 Fiberglass		Threaded <u>X</u>
Blank casing diameter	<u>2</u> in. to <u>15.5</u> ft. Dia	<u>15.5</u> in. to ft. Dia		
Casing height above land surface	<u>0</u> in. weight	<u>716</u> lbs./ft. Wall thickness or gauge No.	<u>154</u>	
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement		
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)	
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS:	From <u>15.5</u> ft. to <u>25.5</u> ft.	From ft. to ft.		
GRAVEL PACK INTERVALS:	From <u>13.5</u> ft. to <u>25.5</u> ft.	From ft. to ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals:	From <u>0</u> ft. to <u>3</u> ft.	From <u>3</u> ft. to <u>13.5</u> ft.	From ft. to ft.	
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
Direction from well?				13 Insecticide storage
				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below)
				<u>Removed Fuel Storage</u>

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>4</u>	<u>Fill Sand</u>			
<u>4</u>	<u>8</u>	<u>Silty Clay</u>			
<u>8</u>	<u>18.5</u>	<u>Clayey Silty</u>			
<u>18.5</u>	<u>25.5</u>	<u>Sand</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)	<u>8-8-96</u>	and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. <u>554</u>	This Water Well Record was completed on (mo/day/yr)	<u>8-29-96</u>
under the business name of <u>Wooster Pumps Well, Inc</u>	by (signature)	<u>Ray C. Wooster</u>