WATER WELL RECORD			Form W	WC-5	Division of	Water Resources App. N	lo	
1 LOCATION OF WATER WELL:		Fraction		Section Numb	er Township No.	Range Number		
County: Sumner			sw 1/4 NE 1/4 NW	1/4 NW 1/4	26 T 34 S R 2 🗀 E 🕟			
Street/Rural Address of Well Location; if unknown, distance & direction					Global Positioning System (GPS) information:			
from nearest town or intersection: If at owner's address, check here .					Latitude: (in decimal degrees)			
					Longitude: (in decimal degrees)			
					Elevation:			
					<u>Datum</u> : ☐ WGS 84, ☐ NAD 83, ☐ NAD 27			
2 WATER WELL OWNER: Larry Pacey					Collection Method:			
RR#, Street Address, Box #: PO Box 527					GPS unit (Make/Model:)			
City, State, ZIP Code : Wellingto			on, KS 67152		Digital Map/Photo, Topographic Map, Land Survey			
Est. Accuracy:								
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 40 ft.								
	SECTION BOX: Depth(s) Groundwater Encountered (1)							
5201	N WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr							
Description Well-successive A - A								
FST VIFID grow Well water was flafter hours numning gr								
W NW NE E Bore Hole Diameter 8								
WELL WATER TO BE USED AS: ☐ Public water supply ☐ Geothermal ☐ Injection well								
Domestic Feedlot Oil field water supply Dewatering Other (Specify below)								
Irrigation								
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No								
S If yes, mo/day/yr sample was submitted								
mile Water well disinfected?								
5 TYPE OF CASING USED: Steel PVC Other								
CASING JOINTS: Glued Clamped Welded Threaded								
Casing diameter .5								
Casing height above land surface. 84 in., Weight 2.42 lbs./ft., Wall thickness or gauge No214								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel								
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)								
Louvered shutter Key punched Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From 20 ft. to 40 ft., From ft. to ft.								
SCREEN-PERFORATED INTERVALS: From								
GRAVEL PACK INTERVALS: From 20 ft. to .40 ft., From ft. to								
From								
6 GROUT MATERIAL: Neat cement Cement grout Denotite Other								
Grout Intervals: From .20								
What is the nearest source of possible contamination:								
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)								
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well								
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well ☐ Unkown								
	tion from well.							
FROM	ТО	LITHOLOG	IC LOG	FROM	TO LITHO	J. LOG (cont.) or PLU	UGGING INTERVALS	
	20 Sand							
20	40 Shale							
						N		
						-1		
							1300	
				LL				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged								
under my jurisdiction and was completed on (mo/day/year) .05/02/2011 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 818 This Water Well Record was completed on (mo/day/year) 95/02/2011								
under the business name of Hobbs Mechanical, Inc. by (signature) A.								
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three eopies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.								
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at								
http://www.kdheks.gov/waterwell/index.html.								
KSA 82a-1212 Check: ✓ White Copy, ☐ Blue Copy, ☐ Pink Copy								