


1 LOCATION OF WATER WELL: County: COMANCHE Fraction: NW 1/4 SW 1/4 SE 1/4 Section Number: 29 Township Number: T 34 S Range Number: R 20 E 10

Distance and direction from nearest town or city street address of well if located within city?

From Protection 2 W 95

2 WATER WELL OWNER: Wayne Woolfolk  
 RR#, St. Address, Box #: Protection, KS  
 City, State, ZIP Code: Protection, KS  
 Board of Agriculture, Division of Water Resources  
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 18.40 ft. ELEVATION: 20 ft. below land surface measured on mo/day/yr

Depth(s) Groundwater Encountered 1. 20 ft. 2. 1.0 ft. 3. 1.0 ft.

WELL'S STATIC WATER LEVEL: 20 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 20 ft. after 1.0 hours pumping 20 gpm

Est. Yield: 20 gpm; Well water was 1.0 ft. after 1.0 hours pumping 20 gpm

Bore Hole Diameter: 1.0 in. to 1.0 ft., and 1.0 in. to 1.0 ft.

WELL WATER TO BE USED AS:  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped  
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
 7 Fiberglass Threaded

Blank casing diameter: 5 in. to 24.50 ft., Dia. 5 in. to 24.50 ft., Dia. 5 in. to 24.50 ft.

Casing height above land surface: 24.50 in., weight 24.50 lbs./ft. Wall thickness or gauge No. 24.50

TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)  
 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 50 ft. to 70 ft., From 50 ft. to 70 ft., From 50 ft. to 70 ft.

GRAVEL PACK INTERVALS: From 20 ft. to 78 ft., From 20 ft. to 78 ft., From 20 ft. to 78 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 0 ft. to 20 ft., From 0 ft. to 20 ft., From 0 ft. to 20 ft.

What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage

Direction from well? South How many feet? 25

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	24	SAND			
25	40	RED CLAY SAND			
41	50	FINE SAND			
51	73	GRAVEL			
74	78	RED CLAY			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-1-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 7411 This Water Well Record was completed on (mo/day/yr) 7-31-90 under the business name of LEAH'S WATER WELL by (signature) RON LEAH