

CORRECTION(S) TO WATER WELL RECORD (WWC-5)  
(to rectify lacking or incorrect information)

County: Clark

Location listed as:

Section-Township-Range: 17-34 S-21 E

Fraction (  $\frac{1}{4}$   $\frac{1}{4}$   $\frac{1}{4}$ ): NE NE NE

Location changed to:

17-34 S-21 W

NE NE NE

Other changes: Initial statements: From Ashland - Jct. 160 & 34 5 miles south  
& 1  $\frac{3}{4}$  east.

Changed to: From Ashland: 6 mi. E. on Hwy. 160 to jct. of 160 & 34,  
7 mi. S. on Hwy 34, 1 mi. E.

Comments: \_\_\_\_\_

verification method: Legal & written descriptions, county ownership map,  
position on plat map, and mapping tool & aerial photo on  
KGS website. initials: DRL date: 1/27/2009

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726  
to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Fraction Section Number Township Number Range Number  
 COUNTY: CLARK NE 1/4 NE 1/4 NE 1/4 17 T 34 S R 21 E

Distance and direction from nearest town or city street address of well if located within city?  
 FROM ASHLAND - JCT. 160 & 34 5 MILES SOUTH & 1 3/4 EAST

2 WATER WELL OWNER: SHUPE, OLIVER Board of Agriculture, Division of Water Resources  
 RR#, St. Address, Box #: Application Number:  
 City, State, ZIP code: ASHLAND, KS 67831-

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL 60 ELEVATION: 0  
 Depth(s) Groundwater Encountered 1. 0 ft. 2. 0 ft. 3. 0 ft.  
 WELL'S STATIC WATER LEVEL 12 ft. below land surface measured on mo/day/yr 07/16/08  
 Pump testdata: Well water was 0 ft. after 0 hours pumping 0 gpm  
 Estimated Yield 10 gpm: Well water was 0 ft. after 0 hours pumping 0 gpm  
 Bore Hole Diameter 15 in. to 60 ft., and in. to 0 ft.  
 WELL WATER TO BE USED AS: DOMESTIC  
 Was a chemical/bacteriological sample submitted to department? No ;  
 If yes, mo/day/yr sample was submitted Water well disinfected? Yes

5 TYPE OF BLANK CASING USED: CERTA LOC CASIN CASING JOINTS: CERTA-LOC  
 Blank casing diameter 8 in. to 60 ft., Dia in. to 0 ft., Dia in. to 0 ft.  
 Casing height above land surface 12 in., weight 200 lbs/ft. Wall thickness or gauge No. 160  
 TYPE OF SCREEN OR PERFORATION MATERIAL: PVC  
 SCREEN OR PERFORATION OPENINGS ARE: SAW CUT

SCREEN PERFORATED INTERVALS: From 10 ft. to 50 ft., From 0 ft. to 0 ft.  
 From 0 ft. to 0 ft., From 0 ft. to 0 ft.  
 GRAVEL PACK INTERVALS: From 10 ft. to 60 ft., From 0 ft. to 0 ft.  
 From 0 ft. to 0 ft., From 0 ft. to 0 ft.

6 GROUT MATERIAL BENTONITE  
 Grout Intervals: From 0 ft. to 10 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft.  
 What is the nearest source of possible contamination: NONE  
 Direction from well? How many feet? 0

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	10	01 TOPSOIL 32 TAN CLAY			
10	25	10 FINE-MEDSAND			
25	35	02 FINE SAND 17 CLAY LAYERS			
35	60	26 RED CLAY			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) 07/16/08 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179 This Water Well Record was completed on (mo/day/yr) 07/24/08 under the business name of JOE'S WELL SERVICE, INC. by (signature) *Julia Cwik*