


1 LOCATION OF WATER WELL: Fraction NE 1/4 NE 1/4 NE 1/4 Section Number 10 Township Number T 34 S Range Number R 24 E
 County: Clack

Distance and direction from nearest town or city street address of well if located within city?

4 N and 3 1/4 E from Englewood

2 WATER WELL OWNER: Henry Gardner
 RR#, St. Address, Box #: Ashtland, KS 67831
 City, State, ZIP Code: Ashtland, KS 67831
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 56 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 23 ft. 2. 23 ft. 3. 23 ft.
 WELL'S STATIC WATER LEVEL 23 ft. below land surface measured on 5-5-92
 Pump test data: Well water was 30 gpm after 1 1/2 hours pumping 30 gpm
 Est. Yield 30 gpm; Well water was 45 ft. after 1 1/2 hours pumping 30 gpm
 Bore Hole Diameter: 8 3/4 in. to 5.6 in. and 5.6 in. to 5.6 in.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 20 ft., Dia 5 in. to 20 ft., Dia 5 in. to 20 ft.
 Casing height above land surface 12 in., weight 12 lbs./ft. Wall thickness or gauge No. 12
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 20 ft. to 56 ft., From 20 ft. to 56 ft., From 20 ft. to 56 ft.
 GRAVEL PACK INTERVALS: From 20 ft. to 56 ft., From 20 ft. to 56 ft., From 20 ft. to 56 ft.

6 GROUT MATERIAL: 1 Neat cement Cement grout 3 Bentonite 4 Other
 Grout intervals: From 5 ft. to 20 ft., From 5 ft. to 20 ft., From 5 ft. to 20 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? S How many feet? 70

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>8</u>	<u>Top soil</u>			
<u>9</u>	<u>17</u>	<u>Sand</u>			
<u>17</u>	<u>32</u>	<u>Clay (brown)</u>			
<u>32</u>	<u>56</u>	<u>Sand, gravel</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-5-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 101 This Water Well Record was completed on (mo/day/yr) 8-4-92 under the business name of Partel Well Drilling, Inc by (signature) Reuben Partel

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T
R
E
W
S
E
C.
1/4
1/4
1/4