WATER WELL RECORD		Form W	WC-5	Division of Wate	r Resources App. N	0.	
1 LOCATION OF WATER WELL: County: Meade		Fraction SE 4NE 4NE	1/4 A) (D) 1/4	Section Number 21	Township No. T 34 S	Range Number R 26	
Street/Rural Address of Well Location; if unknown, distance & direction Global Positioning System (GPS) information:							
		own or intersection: If at o		Latitude: 37.04.747       (in decimal degrees)         Longitude: 100.09.359       (in decimal degrees)         Elevation: 2311       (in decimal degrees)         Datum: ☑ WGS 84, ☐ NAD 83, ☐ NAD 27			
2 WATER WELL OWNER: KU Endow RR#, Street Address, Box #: (>0 Co.			owment Assn.		Collection Method:  ☐ GPS unit (Make/Model: Garmin GPSmap 60)		
			ence, KS 6604	/4	☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey  Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m		
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 160 ft.							
Sist.	TON BOX: Depth(s) Groundwater Encountered (1)						
Pump test data: Well water was .125							
EST. YIELD. 10gpm. Well water was							
W Bore Hole Diameter 8.3/4 in. to .160 ft., and in. to							
WELL WATER TO BE USED AS: □ Public water supply □ Geothermal □ Injection well							
SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)							
Was a chemical/bacteriological sample submitted to Department? Yes V No							
S If yes, mo/day/yr sample was submitted							
water went distincted: [4] Tes 140							
5 TYPE OF CASING USED: Steel PVC Other							
CASING JOINTS: Glued Clamped Welded Threaded							
Casing diameter .5 in. to .120 ft., Diameter in. to ft., Diameter in. to ft.							
Casing height above land surface. 24 in., Weight							
TYPE OF SCREEN OR PERFORATION MATERIAL:  Steel Stainless Steel PVC Other (Specify)							
☐ Steel ☐ Stainless Steel							
SCREEN OR PERFORATION OPENINGS ARE:							
☐ Continuous slot   ☑ Mill slot   ☐ Gauze wrapped   ☐ Torch cut   ☐ Drilled holes   ☐ None (open hole)							
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)							
SCREEN-PERFORATED INTERVALS: From129							
From							
GRAVEL PACK INTERVALS: From 20 ft. to160 ft., From							
From ft. to ft., From ft. to ft.							
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other							
Grout intervals: From 192. It. to 193. It.							
What is the nearest source of possible contamination:  Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)							
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well							
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☑ Oil well/gas well							
Direc	ction from	n well South			from well 2000 fe		
FROM	TO	LITHOLOG	IC LOG	FROM	TO LITHO. LO	OG (cont.) or PLU	GGING INTERVALS
0	4	topsoil					
4	25	brown clay					
25	34	cleachy				·	
34	81	brown clay					
81	95	sand					
95	130	sandy brown clay					
130	140	sand			Original Returned to Sender		
140	145	sandy brown clay					
145	160	sand and gravel			for	Correction	Date: 7//5/IO
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was \( \bigsize \) constructed, \( \bigsize \) reconstructed, or \( \bigsize \) plugged							
under my jurisdiction and was completed on (mo/day/year) .2/25/2019 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 101. This Water Well Record was completed on (mo/day/year) 3/20/2010 under the business name of Bartel Well Drilling, Inc. by (signature)							
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies							
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.  Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include, fee of \$5.00 for each constructed well. Visit us at							
http://www.kdheks.gov/waterwell/index.html.							
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy							