WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: MEADE C60 | Fraction: W2 ¼ SE ¼ SE ¼ | Section Number: 35 | Township Number: T 34S S | Range Number: R 28W E/W

Distance and direction from nearest town or city street address of well if located within city?

16½ MILES SOUTH OF MEADE, KS.

#1 Lester Rhodes

2 WATER WELL OWNER: BEREDCO DRILLING

RR#, St. Address, Box # : 401 E. DOUGLAS, #402

City, State, ZIP Code : WICHITA, KS 67202

Board of Agriculture, Division of Water Resources Application Number: #940274

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N; NW, NE, W, E, SW, SE X, S; 1 Mile

4 DEPTH OF COMPLETED WELL 340 ft. ELEVATION:

Depth(s) Groundwater Encountered 1. 135 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 135 ft. below land surface measured on mo/day/yr 7-26-94

Pump test data: Well water was 150 ft. after 1 hours pumping 95 gpm

Est. Yield 95 gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 9½ in. to 340 ft., and in. to ft.

WELL WATER TO BE USED AS: 1 Domestic 2 Irrigation 3 Feedlot 4 Industrial 5 Public water supply 6 Oil field water supply 7 Lawn and garden only 8 Air conditioning 9 Dewatering 10 Monitoring well 11 Injection well 12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below)

CASING JOINTS: Glued X Clamped Welded Threaded

Blank casing diameter 5 in. to 340 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface 24 in., weight 2.902 lbs./ft. Wall thickness or gauge No. .265 SDR 21

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)

SCREEN-PERFORATED INTERVALS: From 280 ft. to 340 ft., From ft. to ft.

From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 240 ft. to 340 ft., From ft. to ft.

From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other HOLE PLUG

Grout Intervals: From 1 ft. to 20 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)

Direction from well? South How many feet? 175

FROM	TO	LITHOLOGIC LOG
0	2	SANDY CLAY
2	6	SAND
6	46	CLAY
46	73	SANDY CLAY
73	86	CLAY
86	127	SANDY CLAY & CLAY
127	138	SANDY CLAY
138	157	SAND
157	166	CLAY
166	187	SANDY CLAY
187	197	SAND
197	208	CLAY
208	219	SAND
219	234	SANDY CLAY & CLAY
234	283	CLAY

FROM	TO	PLUGGING INTERVALS
283	293	SAND
293	297	CLAY
297	336	SAND
336	340	RED

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-26-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. KWWCL-430 This Water Well Record was completed on (mo/day/yr) 7-26-94 under the business name of HOWARD DRLG.CO.BOX 806 BEAVER, OK 73932 by (signature)

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY T R E/W SEC. ¼ ¼ ¼

#18984