

1 LOCATION OF WATER WELL: County: MEADE	Fraction NW 1/4 SE 1/4 NE 1/4	Section Number 17	Township Number T 34 S	Range Number R 29W E 1W
---	---	-----------------------------	----------------------------------	-----------------------------------

Distance and direction from nearest town or city street address of well if located within city?

15 MILES SOUTH MEADE, KS

2 WATER WELL OWNER: EAGLE CREEK	#1-17 HORACE
RR#, St. Address, Box #: 107 N MARKET STE 509	Board of Agriculture, Division of Water Resources
City, State, ZIP Code: WICHITA, KS 67202	Application Number: 950253

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 300 ft. ELEVATION:
--	--

1 Mile

W E

N S

Depth(s) Groundwater Encountered 1. **70** ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL **70** ft. below land surface measured on mo/day/yr **08-15-95**

Pump test data: Well water was **85** ft. after **1** hours pumping **90** gpm

Est. Yield **90** gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter **9 1/2** in. to **300** ft., and in. to ft.

WELL WATER TO BE USED AS:

1 Domestic	3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
2 Irrigation	4 Industrial	7 Lawn and garden only	10 Monitoring well	

Was a chemical/bacteriological sample submitted to Department? Yes.....No...**X**....; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes **X** No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 5 in. to 300 ft., Dia. in. to ft., Dia. in. to ft.			Threaded
Casing height above land surface 24 in., weight 2.902 lbs./ft. Wall thickness or gauge No. 280 SDR 21			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	9 Drilled holes	
2 Louvered shutter	4 Key punched	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 200 ft. to 300 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 100 ft. to 300 ft., From ft. to ft.			

6 GROUT MATERIAL: 1 Neat cement	2 Cement grout	3 Bentonite	4 Other HOLE PLUG
Grout Intervals: From 0 ft. to 16 ft., From ft. to ft.			
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well	
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage
2 Sewer lines	5 Cess pool	8 Sewage lagoon	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
			13 Insecticide storage
Direction from well? Southwest			How many feet? 200

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	14	SAND			
14	90	CLAY & SAND STREAKS			
90	94	CLAY			
94	98	SANDY CLAY			
98	130	SAND			
130	190	SANDY CLAY & CLAY			
190	238	SANDY CLAY & GRAVEL			
238	250	COARSE SAND & GRAVEL			
250	265	CLAY & SAND STREAKS			
265	290	COARSE SAND & GRAVEL			
290	300	CLAY			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 08-15-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. KWICL-430 This Water Well Record was completed on (mo/day/yr) 08-15-95 under the business name of HOWARD DRUG CO. BOX 806 BEAVER, OK 73932 by (signature) <i>Howard</i>

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.