


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Meade		SE 1/4 SE 1/4 NW 1/4	3	T 34 S	R 29 E (W)
Distance and direction from nearest town or city street address of well if located within city? 12 1/2 SW of Meade, KS--					
2 WATER WELL OWNER: Murfin Drilling			#1-3 Deeds		
RR#, St. Address, Box #: 250 N. Water, #300			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code: Wichita, KS 67202			Application Number: 920309		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 320 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 75 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 75 ft. below land surface measured on mo/day/yr 8/13/92 Pump test data: Well water was 85 ft. after 1 hours pumping 100 gpm Est. Yield 100 gpm Well water was ft. after hours pumping gpm Bore Hole Diameter 9 1/2 in. to 320 ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped			
1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought iron 8 Concrete tile 6 Asbestos-Cement 9 Other (specify below) 7 Fiberglass			
Blank casing diameter 5 in. to 320 ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface 24 in., weight lbs./ft. Wall thickness or gauge No. 032		TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole) 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 240 ft. to 320 ft. From ft. to ft. From ft. to ft. From ft. to ft.		GRAVEL PACK INTERVALS: From 180 ft. to 320 ft. From ft. to ft. From ft. to ft. From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Hole Plug		Grout Intervals: From 1 ft. to 20 ft. From ft. to ft. From ft. to ft.			
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well 11 Fuel storage 15 Oil well/Gas well 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage			
1 Septic tank 4 Lateral lines 7 Pit privy 2 Sewer lines 5 Cess pool 8 Sewage lagoon 3 Watertight sewer lines 6 Seepage pit 9 Feedyard		Direction from well? Southwest How many feet? 160			
FROM TO LITHOLOGIC LOG		FROM TO		PLUGGING INTERVALS	
0	3	Surface Soil		275	288 Clay
3	14	Brown Clay		288	311 Sand
14	29	Sandy Clay		311	320 Pink Sandy Clay
29	64	Clay			
64	73	Sandy Clay			
73	78	Blue and Black Clay			
78	121	Clay			
121	130	Fine Sand			
130	148	Clay w/Sand Streaks			
148	170	Blue Clay			
170	182	Fine Sand			
182	195	Clay w/Sand Streaks			
195	207	Sand			
207	228	Clay w/Sand Streaks			
228	275	Sand and Gravel			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/12/92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. KWWCL-430. This Water Well Record was completed on (mo/day/yr) 8/12/92 under the business name of Howard Drlg. Co. Box 806 BEaver, OK 73932 by (signature)					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					