USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

Adams 1-34 CWW Inv. #12420 / WAY T	WU		Topeka, Kansas 66620
County Fraction	Section	number	Township number Range number
1. Location of well: Meade 1/4 1/4 C-NW1/4	34		τ 314 <u>s</u> R 29 ε/ <u>w</u>
2. Distance and direction from negrest town or city-SQ of Meade Take 3. Own	er of wel	Rain	s & Williamson Oil Co., Inc.
on Siway 23 to Port of Entry-3/4 mi. S-lmi. R.R. or street:435 Page Court, 220 West Douglas Street oddress of Well location if in city. E. thru a cattille guard-3/4 mi. S-1/2 mi. W City, state, zip code: Wichita, Kansas 67202			
4. TO COTE WITH A IN SECTION below: Sketch map: M MEADE LAK		,	6. Bore hole dia 9 in. Completion date 6-21. Well depth 160 ft.
PERtof Entr	γ _ν \ <u>έ</u>	<i>b</i> .	7 Cable tool X_ Rotary Driven Dug
NW NE			Hollow rod Jetted Bored Reverse rotary
W I I I E			8. Use: Domestic Public supply Industry
	200		Irrigation Air conditioning Stock Lawn X Oil field water Other
SW SE	1,		9. Casing: Material Height: Above or below
Into Lo	CAtio	oh .	Threaded Surface in. RMP PVCX Weight 2.78_lbs./ft.
S 1 Mile			RMP PVC X Weight 2.70 lbs./ft. Dia. 5 in. to 190ft. depth Wall Thickness: inches or
5. Type and color of material	From	То	Dia. 5 in. to 380t. depth gage No. 265
			10. Screen: Manufacturer's name
Surface	0	2	Type PVC Dia. 5"
Clay	2	190	
Clay & fine sand		380	Set between 190 ft. and 320 ft. 380 ft. and 160 ft. Gravel pack? Yes Size range of material 1/8-3/16
Clay, Med. to lge. sand		اير	11. Static water level: 190 ft. below land surface Date 6/24/76
			12. Pumping level below land surfaces:
Clay & med. to lge. sand	420	460	ft. after hrs. pumping g.p.m.
			ft. after hrs. pymping g.p.m.
B. R. P.			Estimated maximum yieldg.p.m. 13. Water sample submitted:mo./day/yr.
			YesX_ No Date
			14. Well head completion:
			Pitless adapter <u>28</u> Inches above grade 15. Well grouted? <u>Yes</u>
			With: X Neat cement Bentonite Concrete
		-	Depth: From O ft. to 10 ft.
			16. Nearest source of possible contamination: ft. 100 Direction NE Type 011 well
			Well disinfected upon completion? X Yes No
			17. Pump: X Not installed
			Manufacturer's name
			Length of drop pipe ft. capacityg.p.m.
·			Type: Submersible Turbine
			Jet Reciprocating
(Use a second sheet if needed)		L	Centrifugal Other
18. Elevation: 19. Remarks:			20. Water well contractor's certification:
2495thm			This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Topography: ///			Carlile Water Well Service 118 5
HIII that some state of the sta			Business name License No. Address Box 275, Liberal Ks. 67901
X Upland			Signed Salvard & Means Date 6/30 - 18
Valley			Authorized representative