

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Meade		NE 1/4 NE 1/4 SE 1/4	3	T 34 S	R 29 EW
Distance and direction from nearest town or city street address of well if located within city?					
Reaver 6N., 1E., N on #23 to State Line, approx 8N., W into					
2 WATER WELL OWNER: Sweetman Drilling Co.		#1-3 Hissom			
RR#, St. Address, Box #: 3017 N Cypress		Board of Agriculture, Division of Water Resources			
City, State, ZIP Code: Wichita, Ks 67226-4003		Application Number: 990038			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 360 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 100 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 100 ft. below land surface measured on mo day yr 12-19-97			
		Pump test data: Well water was 168 ft after 1 hours pumping 120 gpm			
		Est. Yield 120 gpm: Well water was ft after hours pumping gpm			
		Bore Hole Diameter 11 in. to 370 ft. and in. to ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
Was a chemical bacteriological sample submitted to Department? Yes No X		If yes, mo day yr sample was submitted			
5 TYPE OF BLANK CASING USED:		Water Well Disinfected? Yes X No			
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below)		CASING JOINTS: Glued X Clamped Welded Threaded			
Blank casing diameter 24 in. to 360 ft. Dia 2.902 in. to ft. Dia		lbs. ft. Wall thickness or gauge No .281 SDR 21			
Casing height above land surface 24 in. weight 2.902					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS From 280 ft. to 360 ft.					
GRAVEL PACK INTERVALS From 160 ft. to 360 ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other		Hole Plug			
Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? Southwest		How many feet? 300			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Topsoil	355	360	Sand
2	17	Sandy Clay	360	370	Clay
17	124	Blue / Brown Clay			
124	138	Sand / Blue Clay			
138	160	Blue / Brown Clay			
160	189	Sand / Blue Clay			
189	198	Blue Clay			
198	207	Sand			
207	274	Blue Clay / Sand Streaks			
274	302	Sand			
302	312	Clay			
312	321	Sand			
321	333	Clay			
333	345	Sand			
345	355	Clay			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo day yr) 12-19-97 and this record is true to the best of my knowledge and belief Kansas					
Water Well Contractor's License No. KWCL - 430 This Water Well Record was completed on (mo day yr) 12-19-97					
under the business name of Howard Drlg. Box 806 Beaver, Ok 73932 by (signature)					