


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Meade	SW 1/4 NE 1/4 NE 1/4	5	T 34 S	R 30 EW

Distance and direction from nearest town or city street address of well if located within city?

9 Miles South of Plains, Kansas

2 WATER WELL OWNER:	Mr. Tom Fisher	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	Box 79	Application Number: ----
City, State, ZIP Code :	Meade, Kansas 67864	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 380 ft. ELEVATION: Slope
	Depth(s) Groundwater Encountered 1. Not available 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 212 ft. below land surface measured on mo/day/yr July 24, 1987
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield 20 gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 10 in. to 380 ft., and in. to ft.
	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
	XXX Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
	Was a chemical/bacteriological sample submitted to Department? Yes No XXX; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes XX No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued XX Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
XXX PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 5 in. to 320 ft., Dia			Threaded
Casing height above land surface 15 in., weight 2.8 lbs./ft. Wall thickness or gauge No. 265			
TYPE OF SCREEN OR PERFORATION MATERIAL:	XXX PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	XXX 8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 320 ft. to 380 ft.		
	From ft. to ft.		
GRAVEL PACK INTERVALS:	From 20 ft. to 380 ft.		
	From ft. to ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	XXX 4 Other Baroid Hole Plug
Grout intervals:	From 0 ft. to 20 ft.			
What is the nearest source of possible contamination: NONE				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well?

How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Topsoil			
2	17	Fine Sand			
17	57	Clay			
57	61	Fine Sand			
61	72	Clay			
72	90	Fine Sand			
90	101	Clay			
101	155	Green Clay			
155	179	Fine Sand			
179	184	Clay			
184	196	Med. to Lar. Sand			
196	199	Green Clay			
199	380	Med. Sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) July 24, 1987 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 252 This Water Well Record was completed on (mo/day/year) August 4, 1987 under the business name of FRIESEN WINDMILL & SUPPLY INC. by (signature)

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.