


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

Holmes #2

CWW Inv. # 12287

1. Location of well:		County Meade	Fraction 1/4 C-NE/4 NW 1/4	Section number 29	Township number T 34 S	Range number R 30 E/W
2. Distance and direction from nearest town or city: 2 miles south of Meade Lake, 5 west, 5 south, 3 1/2 west Street address of well location if in city:				3. Owner of well: Sage Drilling Company R.R. or street: 500 Bitting Bldg. City, state, zip code: Wichita, Kansas 67901		
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 9 in. Completion date 5-6 Well depth 270 ft.		
				7. Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary		
5. Type and color of material		From	To	8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input checked="" type="checkbox"/> Oil field water <input type="checkbox"/> Other		
Surface		0	2	9. Casing: Material <input type="checkbox"/> Height: Above or below Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface 28 in. RMP <input type="checkbox"/> PVC <input checked="" type="checkbox"/> Weight 2.78 lbs./ft. Dia. 5 in. to 110 ft. depth Wall Thickness: inches or Dia. 2 in. to 230 ft. depth gage No. 265		
Sand with clay streaks		2	47	10. Screen: Manufacturer's name sawed perf & Wesco screen		
Fine to small sand		47	135	Type PVC Dia. 5" Slot/gauze .030 Length 70 Set between 110 ft. and 140 ft. 260 230 ft. and 270 268 ft.		
Sandy blue clay		135	230	Gravel pack? Yes Size range of material 1/8 to 3/16		
Small to medium sand		230	270	11. Static water level: mo./day/yr. 115 ft. below land surface Date 5-6-76		
lost circulation		270		12. Pumping level below land surfaces: ft. after hrs. pumping g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield 55 g.p.m.		
				13. Water sample submitted: mo./day/yr. Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Date		
				14. Well head completion: Pitless adapter 28 inches above grade		
				15. Well grouted? yes With Neat cement Bentonite Concrete Depth: From 0 ft. to 10 ft.		
				16. Nearest source of possible contamination: ft. 100 Direction ne Type oilwell Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		
				17. Pump: <input checked="" type="checkbox"/> Not installed Manufacturer's name Model number HP Volts Length of drop pipe ft. capacity g.p.m. Type: Submersible Turbine Jet Reciprocating Centrifugal Other		
				(Use a second sheet if needed)		
18. Elevation:		19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Carlile Water Well 118 Business name License No. Address Box 275, Liberal, Ks. Signed Edward E. Meade Date 6-2- Authorized representative		
Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley						