


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: MEADE	NW 1/4 NW 1/4 NE 1/4	31	T 34 S	R 30W EW

Distance and direction from nearest town or city street address of well if located within city?

15 MILES SOUTHWEST PLAINS, KS

2 WATER WELL OWNER: QUINQUE OPERATING	# 2 ADAMS
RR#, St. Address, Box # : BOX 2738	Board of Agriculture, Division of Water Resources
City, State, ZIP Code : LIBERAL, KS 679052738	Application Number: 940506

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 340 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 70 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 70 ft. below land surface measured on mo/day/yr 12-19-94
	Pump test data: Well water was 90 ft. after 1 hours pumping 35 gpm
	Est. Yield 35 gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 9 1/2 in. to 340 ft., and in. to ft.
	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
	Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 5 in. to 340 ft., Dia. in. to ft., Dia. in. to ft.			Threaded
Casing height above land surface 24 in., weight 2.902 lbs./ft. Wall thickness or gauge No. 280 SDR 21			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
11 Other (specify)			12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 260 ft. to 340 ft., From ft. to ft., From ft. to ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 220 ft. to 340 ft., From ft. to ft., From ft. to ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other	HOLEPLUG
Grout Intervals: From 1 ft. to ft., From 20 ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? Southeast				13 Insecticide storage	
				How many feet? 300	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	19	SAND, GRAVEL & CLAY			
19	28	SANDY GRAVEL			
28	149	BLUE CLAY			
149	152	SAND			
152	157	BLUE CLAY			
157	161	SAND & GRAVEL			
161	252	BLUE CLAY W/SHALE			
252	255	YELLOW CLAY			
255	278	SAND & GRAVEL			
278	285	YELLOW CLAY			
285	323	SAND & GRAVEL			
323	330	CLAY W/RED BED STREAKS			
330	335	SAND & GRAVEL			
335	340	RED BED			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-19-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. KWWCL-430 This Water Well Record was completed on (mo/day/year) 12-19-94 under the business name of HOWARD DRUG CO. BOX 806 BEAVER, OK 73932 by (signature) [Signature]
--