

1 LOCATION OF WATER WELL: County: Seward		Fraction NE 1/4 SW 1/4 NW 1/4	Section Number 21	Township Number T 34 S	Range Number R 32 EW
Distance and direction from nearest town or city street address of well if located within city? Liberal: from 6 way stop light on Hwy 54 83 bypass go 5 E on Bluebell 2.5 N on Arkalon Rd. E into 1st entrance 250' E and 275' S					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Star Development L.C. Rt. 2 Box 294 Liberal, Ks 67901		Lot # 28 Board of Agriculture, Division of Water Resources Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: <div><div>N</div><div>W<div><div>-NW-</div><div>-NE-</div></div>E<div><div>-SW-</div><div>-SE-</div></div>S</div></div>		4 DEPTH OF COMPLETED WELL 260 ft. ELEVATION: Depth(s) Groundwater Encountered 1 212 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 212 ft. below land surface measured on mo/day/yr 12-01-05 Pump test data: Well water was 8.15 ft. after 1 hours pumping 75 gpm Est. Yield 75 gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 1 Domestic 2 Irrigation 3 Feedlot 4 Industrial 5 Public water supply 6 Oil field water supply 7 Domestic (lawn & garden) 8 Air conditioning 9 Dewatering 10 Monitoring well 11 Injection well 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS		5 Wrought iron 6 Asbestos-Cement 7 Fiberglass		8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued X Clamped Welded Threaded	
Blank casing diameter 5 in. to 260 ft. Dia		Casing height above land surface +2 in., weight 3.706 lbs./ft.		Wall thickness or guage No. SDR 21.316	
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless Steel 4 Galvanized Steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-Cement 11 Other (Specify) 12 None used (open hole)		SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Guazed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)			
SCREEN-PERFORATED INTERVALS: From 200 ft. to 260 ft.		GRAVEL PACK INTERVALS: From 60 ft. to 260 ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Hole Plug		Grout Intervals: From 1 ft. to 25 ft.			
What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)		Direction from well? How many feet?			
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS			
0 3 Surface					
3 18 Clay					
18 57 Sandy clay					
57 97 Clay					
97 122 Sandy clay					
122 139 Sand					
139 145 Sandy clay					
145 155 Clay					
155 255 Sand					
255 260 Sand and clay streaks					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-01-05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. KWWCL 430. This Water Well Record was completed on (mo/day/yr) 12-01-05 under the business name of Howard Drilling Co Box 806 Beaver, Ok 73932 by (signature) Howard Drilling Co					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.					