WATER WELL RECORD	Form W	WC-5	Division of Water	Resources App. N		
1 LOCATION OF WATER W	ELL: Fraction	• 4 .	Section Number		Range Number	
County: >pward	1/4 MW/4 ph		28			
Street/Rural Address of Well Location; if unknown, distance & direction			Global Positioning	System (GPS) in	nformation:	
from nearest town or intersection: If at owner's address, check here .			Latitude: (in decimal degrees)			
			Longitude: (in decimal degrees)			
			Elevation:			
2 WATER WELL OWNER:	Fl. V.		Datum: WGS 84, NAD 83, NAD 27			
2 WATER WELL OWNER: Elva Yanez RR#, Street Address, Box #: 5121 R d 0			Collection Method: GPS unit (Make/Model:)			
City, State, ZIP Code :			☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
City, Suite, Ell Code	Liberal, KS 67901		Est. Accuracy: <			
A LOCUTE WELL						
WITH AN "X" IN 4 DEP	TH OF COMPLETED WEL	،Lبج. بخ. بخ.	ft.			
SECTION BOX: Depth(s	s) Groundwater Encountered	(1)	ft. (2)	ft. ((3) ft.	
N WELL'	Depth(s) Groundwater Encountered (1)					
x	Pump test data: Well water wasft. after hours pumping gpm					
NW NE EST. Y	NW NE EST. YIELD					
W E Bore Hole Diameter L S. in. to						
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well						
SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)						
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well						
Was a chemical/bacteriological sample submitted to Department? Yes A No						
S If yes, mo/day/yr sample was submitted						
water v	well disinfected? 🙀 Yes 🗌	No				
5 TYPE OF CASING USED: Steel PVC Other						
CASING JOINTS: 🙀 Glued 🔲 Clamped 🔲 Welded 🔲 Threaded						
Casing diameter						
Casing height above land surfacein., Weightlbs./ft., Wall thickness or gauge No						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
Steel Stainless Steel PVC Other (Specify)						
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)						
Louvered shutter Key punched Wire wrapped Saw cut SCREEN-PERFORATED INTERVALS: From £1.						
From						
From						
From ft. to ft. From ft. to ft.						
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other. Grout Intervals: From ft. to ft., From ft. to ft., From ft. to ft.						
Grout Intervals: From						
What is the nearest source of possible contamination:						
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below)						
Sewer lines						
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well						
	THOLOGIC LOG	FROM	TO LITHO. LC	JG (cont.) or PLU	GGING INTERVALS	
5 01	of soil	-		***		
	<i>y</i>					
90 150 Mrd SA	nd	 				
150 215 Sandy	lay,	 				
215 287 Clay 8	>ahd					
					NY 12 - 1 - 1	
		-				
					100000000000000000000000000000000000000	
				–		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, \square reconstructed, or \square plugged under my jurisdiction and was completed on (mo/day/year)						
under my jurisdiction and was completed on (mo/day/year)						
Kansas Water Well Contractor's License Ng						
under the business name of South west Wind mill by (signature)						
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.						
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at						
http://www.kdheks.gov/waterwell/index.html.						
KSA 82a-1212						