

WATER WELL RECORD Form WWC-5

Original Record Correction Change in Well Use

Division of Water Resources App. No.

Well ID

1 LOCATION OF WATER WELL:

Fraction

Section Number

Township Number

Range Number

County: Seward

1/4 SW 1/4 SW 1/4

34

T 34S

R 22E W

2 WELL OWNER: Last Name: Hernandez

First: Marisela

Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection): If at owner's address, check here: 6 Miles East of Liberal


Business: 701 E Curtis

Address: Liberal

City: Liberal

State: KS ZIP: 67901

3 LOCATE WELL WITH "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 28.7 ft.

Depth(s) Groundwater Encountered: 1) ... ft. 2) ... ft. 3) ... ft., or 4) Dry Well
WELL'S STATIC WATER LEVEL: 21 ft.
Pump test data: Well water was ... ft. after ... hours pumping ... gpm
Estimated Yield: 50 gpm 287
Bore Hole Diameter: 8 in. to ... ft. and ... in. to ... ft.

5 Latitude: ... (decimal degrees)
Longitude: ... (decimal degrees)
Datum: WGS 84 NAD 83 NAD 27
Source for Latitude/Longitude: GPS (unit make/model: ... (WAAS enabled? Yes No)
Land Survey Topographic Map
Online Mapper:

6 Elevation: ... ft. Ground Level TOC
Source: Land Survey GPS Topographic Map
Other:

7 WELL WATER TO BE USED AS:

- 1. Domestic: Household Lawn & Garden Livestock
2. Irrigation
3. Feedlot
4. Industrial
5. Public Water Supply: well ID
6. Dewatering: how many wells?
7. Aquifer Recharge: well ID
8. Monitoring: well ID
9. Environmental Remediation: well ID
10. Oil Field Water Supply: lease
11. Test Hole: well ID
12. Geothermal: how many bores?
13. Other (specify):

Was a chemical/bacteriological sample submitted to KDHE? Yes No
Water well disinfected? Yes No

8 TYPE OF CASING USED: Steel PVC Other
Casing diameter: 5 in. to 28.7 ft.
Casing height above land surface: 12 in. Weight: ... lbs./ft. Wall thickness or gauge No. #200

TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel Fiberglass PVC Brass Galvanized Steel Concrete tile None used (open hole) Other (Specify)

SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify) Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole)

SCREEN-PERFORATED INTERVALS: From 24.7 ft. to 25.7 ft.
GRAVEL PACK INTERVALS: From 15.0 ft. to 25.7 ft.

9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other
Grout Intervals: From 5 ft. to 25 ft. From 1.5 ft. to 1.5 ft.

Nearest source of possible contamination: Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage Sewer Lines Cess Pool Sewage Lagoon Fuel Storage Abandoned Water Well Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well Other (Specify)
Direction from well? North Distance from well? 40 ft.

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHO. LOG (cont.) or PLUGGING INTERVALS. Rows describe soil layers from 0 to 287 ft depth.

11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year) 7-10-14 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 805 This Water Well Record was completed on (mo-day-year) 7-17-14 under the business name of Southwest W. Ind. Inc.