

1 LOCATION OF WATER WELL: Fraction NE Section Number 3 Township Number T 34 S Range Number R 32 E
 County: Seward

Distance and direction from nearest town or city street address of well if located within city?
1/2 mi N of Hayne

2 WATER WELL OWNER: Ben Burtzloff Board of Agriculture, Division of Water Resources
 RR#, St. Address, Box #: Box 134 Application Number:
 City, State, ZIP Code: Liberal, KS 67901

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 260 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 202 ft. 2. . ft. 3. . ft.
 WELL'S STATIC WATER LEVEL 202 ft. below land surface measured on mo/day/yr 3-22-94
 Pump test data: Well water was 202 ft. after 1 hours pumping 30 gpm
 Est. Yield 50 gpm Well water was . ft. after . hours pumping . gpm
 Bore Hole Diameter 8 3/4 in. to 260 ft. and . in. to . ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes . No ; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped .
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded .
 PVC 4 ABS 7 Fiberglass Threaded .
 Blank casing diameter 5 in. to 220 ft., Dia . in. to . ft., Dia . in. to . ft.
 Casing height above land surface 24 in., weight . lbs./ft. Wall thickness or gauge No. 20016
 TYPE OF SCREEN OR PERFORATION MATERIAL: PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) .
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) .
 SCREEN-PERFORATED INTERVALS: From 220 ft. to 260 ft., From . ft. to . ft.
 From . ft. to . ft., From . ft. to . ft.
 GRAVEL PACK INTERVALS: From 20 ft. to 260 ft., From . ft. to . ft.
 From . ft. to . ft., From . ft. to . ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout Bentonite 4 Other .
 Grout Intervals: From 5 ft. to 20 ft., From . ft. to . ft., From . ft. to . ft.
 What is the nearest source of possible contamination:
 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? S How many feet? 3000

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	15	sandy topsoil			
15	25	brown clay			
25	40	sand			
40	70	brown clay			
70	80	white clay			
80	130	sand + gravel			
130	135	yellow clay			
135	260	sand + gravel with streaks of clay			

One-Call 31859

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-23-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 101 This Water Well Record was completed on (mo/day/yr) 3-31-94 under the business name of Bartel W Drilling Inc by (signature) Reuben J. Bartel

OFFICE USE ONLY
T
R
EW
SEC.
1/4
1/4
1/4