


1 LOCATION OF WATER WELL: Fraction SE 1/4 NE 1/4 NE 1/4 Section Number 9 Township Number T 34 S Range Number R 34 EW
 County: SEWARD

Distance and direction from nearest town or city street address of well if located within city?
 FIVE (5) MILES NORTH AND FIVE (5) MILES WEST OF LIBERAL, KS.

2 WATER WELL OWNER: WAYNE WETTSTEIN
 RR#, St. Address, Box #: ROUTE 1, BOX 133 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: LIBERAL, KS 67901 Application Number: 5,195

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 690 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL . . . 131 . . . ft. below land surface measured on mo/day/yr . . . 3/19/93
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter: 26 in. to . . . 690 ft., and in. to ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X
 7 Fiberglass Threaded
 Blank casing diameter . . . 16 in. to . . . 690 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface . . . 12 in., weight . . . 42.5 lbs./ft. Wall thickness or gauge No. . . 250
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From PERF. 230 ft. to . . . 310 ft., From SCREEN 310 ft. to . . . 350 ft.
 From PERF. 350 ft. to . . . 380 ft., From SCREEN 380 ft. to . . . 400 ft.
 GRAVEL PACK INTERVALS: From . . . 20 ft. to . . . 690 ft., From PERF. 400 ft. to . . . 570 ft.
 From SCREEN 570 ft. to . . . 610 ft., From PERF. 610 ft. to . . . 690 ft.

6 GROUT MATERIAL: Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From . . . 0 ft. to . . . 20 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 13 Insecticide storage
 Other (specify below)
 CROPLAND-NOTHING
 IMMEDIATE VICINITY

LITHOLOGIC LOG			PLUGGING INTERVALS		
FROM	TO		FROM	TO	
0	120	SURFACE			
120	160	MED. TO COARSE SAND			
160	200	BROWN & LIGHT CLAY W/SAND			
200	440	MED. TO COARSE SAND			
440	620	FINE TO MED. SAND			
620	690	FINE SAND			
690	707	RED CLAY			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) . . . 3/17/93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. . . 225 This Water Well Record was completed on (mo/day/yr) . . . 3/30/93 under the business name of KIM DRILLING, INC. by (signature) *Kim Drilling, Inc.*

OFFICE USE ONLY
T
R
EW
SEC
1/4
1/4
1/4