

1 LOCATION OF WATER WELL: County: Stevens		Fraction NE 1/4 NE 1/4 NE 1/4		Section Number 6		Township Number T 34 S		Range Number R 35 EW	
Distance and direction from nearest town or city street address of well if located within city? From SW corner of Hugoton - 10 miles east, 4 miles south, 5,250 ft. north & 20 ft. west									
2 WATER WELL OWNER: Bill Dale		RR#, St. Address, Box #: P. O. Box 193		Board of Agriculture, Division of Water Resources					
City, State, ZIP Code: Hugoton, Kansas 67951		Application Number: 42,409							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 510 ft. ELEVATION:							
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL: 142 ft. below land surface measured on mo/day/yr 1-28-97							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield gpm: Well water was ft. after hours pumping gpm							
Bore Hole Diameter: 30 in. to 510 ft., and in. to ft.		WELL WATER TO BE USED AS:							
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)		5 Public water supply 8 Air conditioning 11 Injection well							
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted							
Water Well Disinfected? Yes No X		5 TYPE OF BLANK CASING USED:							
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded		2 PVC 4 ABS 7 Fiberglass Threaded							
Blank casing diameter: 16 in. to 280 ft., Dia. in. to ft., Dia. in. to ft.		Casing height above land surface: 12 in., weight 42.05 lbs./ft. Wall thickness or gauge No. 250							
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement							
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)							
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)							
SCREEN-PERFORATED INTERVALS: From 280 ft. to 510 ft., From ft. to ft.		GRAVEL PACK INTERVALS: From 20 ft. to 510 ft., From ft. to ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other		Grout Intervals: From 0 ft. to 20 ft., From ft. to ft.							
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well							
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)							
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage		Direction from well? How many feet?							
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS		See attached log							
UNABLE TO PROCURE		ATTACHMENT							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-28-97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/yr) 1-28-97 under the business name of Minter-Wilson Drilling Co. Inc. by (signature) Nora Keller									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.									