County: STEVENS 4 NE 4 NE 4 NE 4 NE 4 1 T 34 S R 35 C WELL OWNER: Last Name: NIX First: DONNA Street or Rural Address where well is located (if unknown, dist	Number
County: STEVENS 1/4 NE 1/4 NE 1/4 NE 1/4 1 1 T 34 S R 35 C 2 WELL OWNER: Last Name: NIX First: DONNA Street or Rural Address where well is located (if unknown, dist	Number
2 WELL OWNER: Last Name: NIX First: DONNA Street or Rural Address where well is located (if unknown, dist	
Business: Address: 995 ROAD 28	ck nere.
Address:	
City: LIBERAL State: KS ZIP: 67905	
3 LOCATE WELL 4 DEPTH OF COMPLETED WELL:507 ft. 5 Latitude:	cimal degrees)
WITH "A" IN Denth(s) Groundwater Encountered: 1) # Longitude: (desired dense)	
SECTION BOX: N 2)	
WELL'S STATIC WATER LEVEL: 26/ ft. Source for Latitude/Longitude:	
below land surface, measured on (mo-day-yr) GPS (unit make/model:)	
NWNE □ above land surface, measured on (mo-day-yr)	
Pump test data: Well water was	
W E after hours pumping	
SW SE after hours numping gpm	
Estimated Yield:50gpm 6 Elevation:	
S Bore Hole Diameter:9.7/8 in. to	
1 mile in. to ft. Other	
7 WELL WATER TO BE USED AS:	
1. Domestic: 5. ☐ Public Water Supply: well ID	
Household 6. □ Dewatering: how many wells?	••
Livestock 8. Monitoring: well ID	
2. ☐ Irrigation 9. Environmental Remediation: well ID	
3. ☐ Feedlot ☐ Air Sparge ☐ Soil Vapor Extraction b) Open Loop ☐ Surface Discharge ☐ Inj	
4. Industrial Recovery Injection 13. Other (specify):	
Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted:	
Water well disinfected? ■ Yes □ No	
8 TYPE OF CASING USED: ☐ Steel ■ PVC ☐ Other	
Casing diameter	
Casing height above land surface 18 in. Weight bs./ft. Wall thickness or gauge No. SDR 21 lbs./ft.	
TYPE OF SCREEN OR PERFORATION MATERIAL: ☐ Steel ☐ Stainless Steel ☐ Fiberglass ■ PVC ☐ Other (Specify)	
☐ Steel ☐ Stainless Steel ☐ Fiberglass ☐ PVC ☐ Other (Specify) ☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:	
☐ Continuous Slot	
☐ Louvered Shutter ☐ Key Punched ☐ Wire Wrapped ☐ Saw Cut ☐ None (Open Hole)	
SCREEN-PERFORATED INTERVALS: From	
GRAVEL PACK INTERVALS: From	
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other	
Grout Intervals: From	
Nearest source of possible contamination: ■ Septic Tank □ Lateral Lines □ Pit Privy □ Livestock Pens □ Insecticide Storage	
Sewer Lines	ell
□ Watertight Sewer Lines □ Seepage Pit □ Feedyard □ Fertilizer Storage □ Oil Well/Gas Well	
☐ Other (Specify)	
10 FROM TO LITHOLOGIC LOG FROM TO LITHO. LOG (cont.) or PLUGGING II	INTERVALS
0 3 TOP SOIL 430 440 MED SAND	
3 50 SANDY CLAY 440 507 FINE SAND AND CLAY	
50 60 MED SAND	
60 100 SANDY CLAY W/ MED SAND	
100 210 CLAY AND SANDY CLAY	
210	
365 385 MED SAND 385 430 SANDY CLAY AND FINE SAND	
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged	
under my jurisdiction and was completed on (mo-day-year) .5/19/16 and this record is true to the best of my knowledge and belief.	
Kansas Water Well Contractor's License No. 805 This Water Well Record was completed on (movday-year) .5/26/16	
under the business name of SQUTHWEST WINDMILL Signature Signature	
Mail 1 white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health and Environment, Bureau of Water, GWTS Section,	
1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone 785-296-552	/10/2015