


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well: County: <u>Stevens</u> Fraction: <u>SW 1/4 SW 1/4 SW 1/4</u> Section number: <u>2</u> Township number: <u>T 34</u> S Range number: <u>R 35</u> E/W			
2. Distance and direction from nearest town or city: <u>13 East H So.</u> Street address of well location if in city: <u>of Hugoton, Ks</u>		3. Owner of well: <u>Warren SPIKES</u> R.R. or street: City, state, zip code: <u>HUGOTON, Kansas 67951</u>	
4. Locate with "X" in section below: N W E S 1 Mile Sketch map: 		6. Bore hole dia. <u>10</u> in. Completion date <u>12-5-76</u> Well depth <u>360</u> ft.	
5. Type and color of material		7. ☒ Cable tool ☒ Rotary ☐ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☐ Bored ☐ Reverse rotary	
From To		8. Use: ☒ Domestic ☐ Public supply ☐ Industry ☐ Irrigation ☐ Air conditioning ☐ Stock ☐ Lawn ☐ Oil field water ☐ Other	
silty silt to gumbo		9. Casing: Material ☐ Height: Above or below Threaded ☐ Welded ☐ Surface <u>12</u> in. RMP ☐ PVC <u>SCH 40</u> Weight ☐ lbs./ft. Dia. <u>5</u> in. to <u>360</u> ft. depth Wall Thickness: inches or Dia. ☐ in. to ☐ ft. depth gage No. <u>250</u>	
Gumbo dark		10. Screen: Manufacturer's name <u>Slocum</u> Type <u>saw cut</u> Dia. <u>5"</u> Slot/gauze <u>1/8</u> Length <u>40'</u> Set between <u>140</u> ft. and <u>160</u> ft. <u>340</u> ft. and <u>360</u> ft. Gravel pack? ☒ Size range of material <u>1/4 3/16</u>	
Sand - fine - white		11. Static water level: ☐ mo./day/yr. <u>115</u> ft. below land surface Date <u>12-5-76</u>	
sand - fine reddish / some clay +		12. Pumping level below land surfaces: <u>120</u> ft. after <u>2</u> hrs. pumping <u>18</u> g.p.m. ☐ ft. after ☐ hrs. pumping ☐ g.p.m. Estimated maximum yield ☐ g.p.m.	
caliche nod cores		13. Water sample submitted: ☐ mo./day/yr. Yes ☒ No Date ☐	
caliche w/ some sand & clay balls		14. Well head completion: ☒ Pitless adapter <u>12</u> inches above grade	
Sand + Gravel brown		15. Well grouted? ☒ With: ☐ Neat cement ☐ Bentonite ☒ Concrete Depth: From <u>4</u> ft. to <u>14</u> ft.	
Clays w/ hard rock stringers		16. Nearest source of possible contamination: ☐ ft. ☐ Direction ☐ Type ☐ Well disinfected upon completion? ☒ Yes ☐ No	
Clay stringers w/ clay balls + sand		17. Pump: Manufacturer's name <u>Flint + Walling</u> Not installed Model number <u>108A15</u> HP <u>1</u> Volts <u>230</u> Length of drop pipe <u>160</u> ft. capacity <u>15</u> g.p.m. Type: ☒ Submersible ☐ Turbine ☐ Jet ☐ Reciprocating ☐ Centrifugal ☐ Other	
Clay shels + Gravel intermittently		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. <u>Slocum Well Drilling 127</u> Business name License No. Address <u>HUGOTON Kansas</u> Signed <u>Paul Slocum</u> Date <u>12-21</u> Authorized representative	
Clay balls + caliche - limy			
Clay stringers w/ caliche + Gravel			
Clay stringers			
Clay balls - tan - containing silt (loose)			
Gravel w/ sand			
(Use a second sheet if needed)			
18. Elevation: Topography: ☐ Hill ☐ Slope ☒ Upland ☐ Valley		19. Remarks:	