

LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Stevens	SW 1/4 SW 1/4 SE 1/4	30	T 34 S	R 36 EW

Distance and direction from nearest town or city street address of well if located within city? Go West on 2nd Street Road to Hooker- Moscow jct. go on West 4 miles 1 mi North 1/2 mi East into location.

WATER WELL OWNER: Donald Kinser Mobil Oil Corp.

RR#, St. Address, Box #: RFD #1 Board of Agriculture, Division of Water Resources

City, State, ZIP Code: Hugoton, Kansas 67951 Application Number: T 85-380

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N			
	NW	NE	
W			E
	SW	SE	
		X	
		S	

DEPTH OF COMPLETED WELL: 325 ft. ELEVATION: 199 ft.

Depth(s) Groundwater Encountered 1. 199 ft. 2. 126 ft. 3. 11 ft.

WELL'S STATIC WATER LEVEL 126 ft. below land surface measured on mo/day/yr 2/22/85

Pump test data: Well water was 11 ft. after 325 hours pumping 11 gpm

Est. Yield 11 gpm: Well water was 11 ft. after 325 hours pumping 11 gpm

Bore Hole Diameter 11 in. to 325 ft., and 11 in. to 325 ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	9 Oil field water supply
2 Irrigation	4 Industrial	10 Dewatering
	7 Lawn and garden only	12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted No

Water Well Disinfected? Yes No

TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>No</u> Clamped <u>No</u>
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded <u>No</u>
		7 Fiberglass		Threaded <u>No</u>

Blank casing diameter 11 in. to 325 ft., Dia 11 in. to 325 ft., Dia 11 in. to 325 ft.

Casing height above land surface 11 in., weight 11 lbs./ft. Wall thickness or gauge No. 11

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
				12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 11 ft. to 325 ft., From 11 ft. to 325 ft., From 11 ft. to 325 ft.

GRAVEL PACK INTERVALS: From 11 ft. to 325 ft., From 11 ft. to 325 ft., From 11 ft. to 325 ft.

GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other No

Grout Intervals: From 11 ft. to 325 ft., From 11 ft. to 325 ft., From 11 ft. to 325 ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? No How many feet? No

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
		Log for plugging water well			
0	4	dirt .79 cu. feet of dirt			
4	14	cement 1.96 cu. feet of cement			
14	116	sand 20.02 cu. feet of sand			
116	126	cement 1.96 cu. feet of cement			
126	325	sand 19.06 cu. feet of sand			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) February 3, 1987 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 118 This Water Well Record was completed on (mo/day/yr) February 6, 1987

under the business name of Carlile Water Well Service, Inc. by (signature) [Signature]