

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County	Stevens	SE 1/4 SE 1/4 NW 1/4	33	T 34 S	R 37 E
Distance and direction from nearest town or city street address of well if located within city?					
From southwest corner of Hugoton - 9 miles south, 1 mile east, 2,750 ft. north & 3,090 ft. west					
2 WATER WELL OWNER:		Danny Price and Donnie Knier			
RR#, St. Address, Box # :		502 E. 15th St.			
City, State, ZIP Code :		Hugoton, Kansas 67951			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 685 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 153 ft. below land surface measured on mo/day/yr 4/28/98			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 26 in. to 685 ft., and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR)		Welded			
2 PVC 4 ABS		Threaded			
Blank casing diameter 16 in. to 600 ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface 12 in., weight 42.05 lbs./ft. Wall thickness or gauge No. 250					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 600 ft. to 685 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 20 ft. to 685 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage N/A					
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
		See attached log			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/6/98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/yr) 5/21/98 under the business name of Minter-Wilson Drilling Co., Inc. by (signature) Nora Keller					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					

*The
Professionals*

MINTER-WILSON DRILLING CO.

Irrigation
and Domestic
Water Systems
Complete Installation
and Repairing

INCORPORATED

Phone 276-8269 • P.O. Box A • GARDEN CITY, KANSAS 67846

Donnie Knier
Stevens County
2/20/98

Location: NW $\frac{1}{4}$ 33-34-37 - Hugoton West Side - 9 miles south, $\frac{1}{2}$ mile east,
 $\frac{1}{2}$ mile north & 336 ft. north

Static Water Level - 190'

Test #1

0' to 4' - Top soil
4' to 12' - Gray clay
12' to 29' - Brown clay 01
29' to 95' - Brown sandy clay 04
95' to 101' - Fine to medium sand 05
101' to 118' - Brown sandy clay 04
118' to 126' - Cemented sand - hard pull down 200 05
126' to 155' - Brown sandy clay 04
155' to 164' - Fine to medium sand 05
164' to 201' - Brown sandy clay 04
201' to 220' - Fine to medium sand and gravel 17
220' to 235' - Brown sandy clay 04
235' to 254' - Fine to medium sand 05
254' to 261' - Brown sandy clay
261' to 274' - Brown sandy clay - 15% gravel streak 04
274' to 410' - Brown clay
410' to 436' - Brown blue clay mixed
436' to 545' - Blue clay
545' to 600' - Blue brown clay mixed 01
600' to 610' - Fine to medium sand and gravel 17
610' to 616' - Brown clay 01
616' to 629' - Fine to medium sand and gravel 17
629' to 636' - Brown clay 01
636' to 680' - Fine to medium sand and gravel - small yellow rock mixed - tight 17
680' to 710' - Red bed 19

(680' to 681' - Hard spot 500)
Red rock