

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number						
County: <b>STEVENS</b>		<b>NW</b> 1/4 <b>NE</b> 1/4 <b>SE</b> 1/4	<b>9</b>	<b>T 34 S</b>	<b>R 38W E/W</b>						
Distance and direction from nearest town or city street address of well if located within city? <b>WEST ON 2nd ST. TO RD 7, 4.5 NORTH &amp; WEST INTO LOC.</b>											
2 WATER WELL OWNER: <b>SEABOARD FARMS CO.</b>		<b>"HOLCOMB"</b> Board of Agriculture, Division of Water Resources									
RR#, St. Address, Box #: <b>P.O. BOX 1207</b>		Application Number:									
City, State, ZIP Code: <b>GUYMON, OK 73942</b>											
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <b>420</b> ft. ELEVATION:									
<div style="text-align: center;">N 1 Mile W E S</div> <table border="1" style="margin: auto; text-align: center;"><tr><td> </td><td> </td></tr><tr><td>NW</td><td>NE</td></tr><tr><td>SW</td><td>SE</td></tr></table>				NW	NE	SW	SE	Depth(s) Groundwater Encountered 1. <b>220</b> ft. 2.     ft. 3.     ft.			
		NW	NE								
		SW	SE								
WELL'S STATIC WATER LEVEL <b>220</b> ft. below land surface measured on mo/day/yr <b>02-29-96</b>											
Pump test data: Well water was <b>240</b> ft. after <b>1</b> hours pumping <b>100</b> gpm											
Est. Yield <b>100</b> gpm: Well water was     ft. after     hours pumping     gpm											
Bore Hole Diameter <b>11</b> in. to <b>420</b> ft., and     in. to     ft.											
WELL WATER TO BE USED AS:											
1 Domestic     3 Feedlot     6 Oil field water supply     9 Dewatering     12 Other (Specify below)											
2 Irrigation     4 Industrial     7 Lawn and garden only     10 Monitoring well											
Was a chemical/bacteriological sample submitted to Department? Yes.....No..... <b>X</b> .....; If yes, mo/day/yr sample was submitted											
Water Well Disinfected? Yes <b>X</b> No											
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued <b>X</b> Clamped									
1 Steel     3 RMP (SR)		Welded									
2 <b>PVC</b> 4 ABS		Threaded									
5 Wrought iron     8 Concrete tile											
6 Asbestos-Cement     9 Other (specify below)											
7 Fiberglass											
Blank casing diameter <b>6</b> in. to <b>420</b> in. Dia.		in. to     ft. Dia.									
Casing height above land surface <b>24</b> in. weight <b>2.902</b> lbs./ft. Wall thickness or gauge No. <b>280 SDR 21</b>											
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 <b>PVC</b> 10 Asbestos-cement									
1 Steel     3 Stainless steel     5 Fiberglass     8 RMP (SR)		11 Other (specify)									
2 Brass     4 Galvanized steel     6 Concrete tile     9 ABS		12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:		8 <b>Saw cut</b> 11 None (open hole)									
1 Continuous slot     3 Mill slot     5 Gauzed wrapped		9 Drilled holes									
2 Louvered shutter     4 Key punched     6 Wire wrapped		10 Other (specify)									
3 Torch cut											
SCREEN-PERFORATED INTERVALS: From <b>360</b> ft. to <b>420</b> ft.		ft. to     ft.									
GRAVEL PACK INTERVALS: From <b>260</b> ft. to <b>420</b> ft.		ft. to     ft.									
6 GROUT MATERIAL: 1 Neat cement     2 Cement grout     3 Bentonite     4 <b>HOLE PLUG</b>											
Grout Intervals: From <b>0</b> ft. to <b>16</b> ft.		ft. to     ft.									
What is the nearest source of possible contamination:		10 Livestock pens     14 Abandoned water well									
1 Septic tank     4 Lateral lines     7 Pit privy     11 Fuel storage     15 Oil well/Gas well		12 Fertilizer storage     16 Other (specify below)									
2 Sewer lines     5 Cess pool     8 Sewage lagoon     13 Insecticide storage											
3 Watertight sewer lines     6 Seepage pit     9 Feedyard											
Direction from well?		How many feet?									
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS						
0	2	TOP SANDY CLAY	300	317	SAND						
2	22	SANDY CLAY	317	322	CLAY						
22	60	CLAY & SANDY CLAY	322	333	SANDY CLAY						
60	96	CLAY	333	350	SAND						
96	102	SANDY CLAY & SAND	350	362	SAND & SANDY CLAY						
102	120	COARSE SAND	362	372	SAND						
120	134	SANDY CLAY	372	390	SAND W/PINK CLAY						
134	164	COARSE SAND	390	418	SAND						
164	190	COARSE SAND & CLAY STREAKS	418	420	CLAY						
190	198	SMALL GRAVEL									
198	217	CLAY & SANDY CLAY									
217	255	CLAY									
255	265	SANDY CLAY									
265	279	SANDY CLAY & SAND									
279	300	SAND & CLAY STREAKS									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <b>02-29-96</b> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <b>KWCL-430</b> This Water Well Record was completed on (mo/day/yr) <b>02-29-96</b> under the business name of <b>HOWARD DRUG CO. BOX 806 BEAVER, OK 73932</b> by (signature) <i>Howard Drug Co.</i>											