			WAT		Form WWC-5	KSA 82	a-1212			
	ON OF WAT	••	Fraction		_ ^ ^	tion Number			Range Number	
County:	STEVEN	ND		/4 NW 1/4 X	1/4 29		т 34	S	R 38 KW	
	nd direction ND ONE-H			address of well if locate H AND ONE (1) N		OF FETT	ERITA.			
2 WATER	WELL OW	NER: STEV	E MORRIS							
	Address, Box		TRINDLE ST	REET			Board of Agr	riculture. D	Division of Water Resources	
City, State,	ZIP Code	: HUGO	TON, KS	67951		Application Number: 41,789				
LOCATE	WELL'S LO	CATION WITH								
	IN SECTION	BUX:							ft.	
WELL'S STATIC WATER LEVEL 155 ft. below land surface measured on mo/day/yr 11/15/95 gp										
Est. Yield gpm: Well water was ft. after hours pumping Bore Hole Diameter 26 in. to 627 ft., and in. to									mping gpm	
╦ ₩ ┝──────────────────────── ┃▐┃										
≥ 2	ا ا	▼	•				•		•	
-	- SW	SE	Domesti		7 Lawn and o	er supply	10 Monitoring well	12 (Other (Specify below)	
	!	!		•					mo/day/yr sample was sub-	
ł L			mitted	i/bacteriological sample s	submitted to De	•	ater Well Disinfected	-	No	
5 TYPE C	F BLANK C	ASING USED:	Timeou	5 Wrought iron	8 Concre				I Clamped	
) Ste		3 RMP (S	R)	6 Asbestos-Cement		specify belo			ed X	
0.00	_	4.400	•	·				T L		
Blank casir	ng diameter	16	.in. to 627	, ft., Dia	in. to		ft., Dia	<i>.</i> i	n. to ft.	
Blank casing diameter 16 in to 627 ft., Dia in to ft. Casing height above land surface 12 in., weight 42.5 lbs./ft. Wall thickness or gauge No. •250										
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement									nt	
1 Steel 3 Stainless steel 5 Fiberglass					8 RM	P (SR)	11 Other	her (specify)		
2 Brass 4 Galvanized steel 6 Concrete tile					9 AB:	9 ABS 12 N		one used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed						ped 8 Saw cut		11 None (open hole)		
1 Continuous slot 3Mill slot 6 Wire wrapped 9 Drilled holes										
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)										
SCREEN-PERFORATED INTERVALS: From PERF. 326 ft. to 366 ft., From SCREEN 366 ft. to 406 ft.										
From PERF . 406 ft. to 586 ft., From SCREEN 586 ft. to 626 ft. GRAVEL PACK INTERVALS: From 20 ft. to 627 ft., From ft. to ft.										
G	RAVEL PAC	CK INTERVALS:							1	
		\sim	From							
6 GROUT MATERIAL: 1 leat cement 2 Cement grout 3 Bentonite 4 Other										
Grout Intervals: From 0ft. to 20										
		urce of possible		7.5%		10 Livestock pens		14 Abandoned water well		
	•	4 Late		7 Pit privy						
2 Sewer lines 5 Cess por 3 Watertight sewer lines 6 Seepag					oon	_		6Other (specify below) CROPLAND-NOTHING		
	-	er lines 6 Seep	page pit	e pit 9 Feedyard		13 Insecticide storage How many feet?		IMMEDIATE VICINITY		
Direction for FROM	rom well?		LITHOLOGIC	2106	FROM	TO TO			NTERVALS	
0	220	SURFACE	SAND & CI		THOM				***************************************	
220	300		AY W/FINE							
300	380		MED. SAND	THE RESERVE OF THE PARTY OF THE						
380	460		COARSE SAN	ND		er e				
460	580		MED. SAND			ANT THREE IT IS				
580	625		MED. COARS	SE SAND						
625	640	RED & BR	ROWN CLAY-I	TIRM						
				THE THE STATE OF T		******	No. 1800 - Law (1880) S. M. E. Lawley (1800) S. Law (1880) S. Lawley (1800) S. L. F. F. C. L. F. F. C. L. F. F. F. C. L. F.		A.S. NALISER VV. INS.	
				1779 C 184						
7 CONTE	RACTOR'S C	R LANDOWNE	R'S CERTIFICA	TION: This water well w	as (1) constru	cted, (2) red	constructed, or (3) plu	igged und	ler my jurisdiction and was	
completed	on (mo/day/	year)	11/15/95			and this red	ord is true to the best	of my kno	owledge and belief. Kansas	
Water Wel	Contractor's	s License No	225	This Water W	Vell Record wa	s completed	I on (mg/day/yr)	3/14/90		
under the l	business nar	me of KTM	DRILLING,	INC.		by (sign	ature)	W [1	Links	