	NN 1/4 NN 1/4 NN 1/4 ; 35 ; T 34 S ; R 38 N nearest town or city street address of well if located within city? 3 MILES EAST OF FETERITA
RR#, St. Address, Box # : R	WHEELER FARMS RRI BOX 69 Board of Agriculture, Division of Water Resources
City, State, ZIP code : F	HUGOTON, KS 67951- Application Number: 42,449
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	
\	: WELL'S STATIC WATER LEVEL 190 ft. below land surface measured on mo/day/yr 08/26; Pump testdata: Well water was 203 ft. after 4 hours pumping 1600
	: : Estimated Yield 1600 gpm: Well water was 0 ft. after 0 hours pumping 0
	: : : : : : : : : : : : : : : : : : :
	; ; well water to be used as: 02 irrigation
; S₩ SE	; Was a chemical/bacteriological sample submitted to department? No ;
TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land su TYPE OF SCREEN OR PERFORATI	O1 STEEL CASING JOINTS: WELDED 16 in. to 649 ft., Dia in. to 0 ft., Dia in. to 0 ft. 17 in., weight 42 lbs/ft. Wall thickness or gauge No250 18 In. to 18 STEEL
TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land su TYPE OF SCREEN OR PERFORATI	O1 STEEL CASING JOINTS: WELDED 16 in. to 649 ft., Dia in. to 0 ft., Dia in. to 0 ft. 17 inface 12 in., weight 42 lbs/ft. Wall thickness or gauge No250 18 inface 10 STEEL 19 inface 10 STEEL 19 inface 10 STEEL
TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land su TYPE OF SCREEN OR PERFORATI SCREEN OR PERFORATION OPENI SCREEN PERFORATED INTERVALS	O1 STEEL CASING JOINTS: WELDED 16 in. to 649 ft., Dia in. to 0 ft., Dia in. to 0 ft. 17 in., weight 42 lbs/ft. Wall thickness or gauge No250 18 In. to 18 STEEL 19 In. to 280 ft. to 410 ft., From 542 ft. to 552 ft. 18 In. to 570 ft.
TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land su TYPE OF SCREEN OR PERFORATION OPENI SCREEN OR PERFORATION OPENI SCREEN PERFORATED INTERVALS GRAVEL PACK INTERVALS GROUT MATERIAL 03 BENTON Grout Intervals: From	O1 STEEL CASING JOINTS: WELDED 16 in. to 649 ft., Dia in. to 0 ft., Dia in. to 0 ft. 17 in., weight 42 lbs/ft. Wall thickness or gauge No250 18 INGS ARE: 01 CONT. SLOT 19: From 280 ft. to 410 ft., From 542 ft. to 552 ft. 19: From 420 ft. to 530 ft., From 560 ft. to 570 ft. 19: From 20 ft. to 643 ft., From 0 ft. to 0 ft. 10: From 0 ft. to 0 ft., From 0 ft. to 0 ft. 10: From 0 ft. to 0 ft., From 0 ft. to 0 ft. 10: From 0 ft. to 0 ft., From 0 ft. to 0 ft.
TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land su TYPE OF SCREEN OR PERFORATION OPENI SCREEN OR PERFORATION OPENI GRAVEL PACK INTERVALS GROUT MATERIAL O3 BENTON Grout Intervals: From	O1 STEEL CASING JOINTS: WELDED 16 in. to 649 ft., Dia in. to 0 ft., Dia in. to 0 ft. 17 in., weight 42 lbs/ft. Wall thickness or gauge No250 18 in. to 649 ft., Dia in. to 0 ft., Dia in. to 0 ft. 19 in. to 649 ft., Dia in. to 0 ft. 10 in. to 649 ft., Dia in. to 0 ft. 10 in. to 649 ft., Dia in. to 0 ft. 10 in. to 643 ft., From 542 ft. to 552 ft. 11 in. to 0 ft. 12 in. to 0 ft. 13 in. to 0 ft. 14 in. to 0 ft. 15 in. to 0 ft. 16 in. to 0 ft. 17 in. to 0 ft. 18 in. to 0 ft. 19 in. to 0 ft. 10 in.
TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land su TYPE OF SCREEN OR PERFORATI SCREEN OR PERFORATION OPENI SCREEN PERFORATED INTERVALS GRAVEL PACK INTERVALS GROUT MATERIAL 03 BENTON Grout Intervals: From What is the nearest source Direction from well? FROM ; TO ;	O1 STEEL CASING JOINTS: WELDED 16 in. to 649 ft., Dia in. to 0 ft., Dia in. to 0 ft. 17 in. to 649 ft., Dia in. to 0 ft., Dia in. to 0 ft. 18 in. to 649 ft., Dia in. to 0 ft. 19 in. to 649 ft., Dia in. to 0 ft. 10 in. to 649 ft., Dia in. to 0 ft. 10 in. to 649 ft., Dia in. to 0 ft. 10 in. to 0 ft. 11 in. to 0 ft. 12 in. to 0 ft. 13 in. to 0 ft. 14 in. to 0 ft. 15 in. to 0 ft. 16 in. to 0 ft. 17 in. to 0 ft. 18 in. to 0 ft. 19 in. to 0 ft. 10 in. to 0 ft. 10 in. to 0 ft. 11 in. to 0 ft. 12 in. to 0 ft. 13 in. to 0 ft. 14 in. to 0 ft. 15 in. to 0 ft. 16 in. to 0 ft. 17 in. to 0 ft. 18 in. to 0 ft. 19 in. to 0 ft. 10 in
TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land su TYPE OF SCREEN OR PERFORATI SCREEN OR PERFORATION OPENI SCREEN PERFORATED INTERVALS GRAVEL PACK INTERVALS GROUT MATERIAL O3 BENTON Grout Intervals: From What is the nearest source Direction from well? FROM ; TO ; O ; 200 ; O5 SAND	O1 STEEL CASING JOINTS: WELDED 16 in. to 649 ft., Dia in. to 0 ft., Dia in. to 0 ft. 17 in., weight 42 lbs/ft. Wall thickness or gauge No250 18
TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land su TYPE OF SCREEN OR PERFORATI SCREEN OR PERFORATION OPENI SCREEN PERFORATED INTERVALS GRAVEL PACK INTERVALS GROUT MATERIAL O3 BENTON Grout Intervals: From What is the nearest source Direction from well? FROM: TO: O: 200: 05 SAND 200: 220: 04 SAND	O1 STEEL CASING JOINTS: WELDED 16 in. to 649 ft., Dia in. to 0 ft., Dia in. to 0 ft. 17 in. to 649 ft., Dia in. to 0 ft., Dia in. to 0 ft. 18 in. to 649 ft., Dia in. to 0 ft. 19 in. to 649 ft., Dia in. to 0 ft. 10 in. to 649 ft., Dia in. to 0 ft. 10 in. to 649 ft., Dia in. to 0 ft. 10 in. to 0 ft. 11 in. to 0 ft. 12 in. to 0 ft. 13 in. to 0 ft. 14 in. to 0 ft. 15 in. to 0 ft. 16 in. to 0 ft. 17 in. to 0 ft. 18 in. to 0 ft. 19 in. to 0 ft. 10 in. to 0 ft. 10 in. to 0 ft. 11 in. to 0 ft. 12 in. to 0 ft. 13 in. to 0 ft. 14 in. to 0 ft. 15 in. to 0 ft. 16 in. to 0 ft. 17 in. to 0 ft. 18 in. to 0 ft. 19 in. to 0 ft. 10 in
TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land su TYPE OF SCREEN OR PERFORATION OPENI SCREEN OR PERFORATION OPENI SCREEN PERFORATED INTERVALS GRAVEL PACK INTERVALS GROUT MATERIAL O3 BENTON Grout Intervals: From What is the nearest source Direction from well? FROM : TO : O : 200 : O5 SANI 200 : 220 : O4 SANI 220 : 240 : O7 FINE 240 : 260 : O1 CLAN	O1 STEEL CASING JOINTS: WELDED 16 in. to 649 ft., Dia in. to 0 ft., Dia in. to 0 ft. 17 inface 12 in., weight 42 lbs/ft. Wall thickness or gauge No250 18
TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land su TYPE OF SCREEN OR PERFORATI SCREEN OR PERFORATION OPENI SCREEN PERFORATED INTERVALS GRAVEL PACK INTERVALS GROUT MATERIAL O3 BENTON Grout Intervals: From What is the nearest source Direction from well? FROM : TO : O : 200 : O5 SAND 200 : 220 : O4 SAND 220 : 240 : O7 FINE 240 : 260 : O1 CLAY 260 : 280 : O4 SAND	O1 STEEL CASING JOINTS: MELDED 16 in. to 649 ft., Dia in. to 0 ft., Dia in. to 0 ft. 17 inface 12 in., weight 42 lbs/ft. Wall thickness or gauge No250 18
TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land su TYPE OF SCREEN OR PERFORATION OPENI SCREEN OR PERFORATION OPENI SCREEN PERFORATED INTERVALS GRAVEL PACK INTERVALS GROUT MATERIAL O3 BENTON Grout Intervals: From What is the nearest source Direction from well? FROM : TO : O : 200 : O5 SAND 200 : 220 : O4 SAND 200 : 220 : O4 SAND 240 : 260 : O1 CLAY 260 : 280 : O4 SAND 280 : 300 : O7 FINE	O1 STEEL CASING JOINTS: MELDED 16 in. to 649 ft., Dia in. to 0 ft., Dia in. to 0 ft. 17 irface 12 in., weight 42 lbs/ft. Wall thickness or gauge No250 18
TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land su TYPE OF SCREEN OR PERFORATION OPENI SCREEN OR PERFORATION OPENI SCREEN PERFORATED INTERVALS GRAVEL PACK INTERVALS GROUT MATERIAL O3 BENTON Grout Intervals: From What is the nearest source Direction from well? FROM TO O 200 O5 SANI 200 220 O4 SANI 220 240 O7 FINE 240 260 O1 CLAN 260 280 O4 SANI 280 300 O7 FINE 300 320 O5 SANI	O1 STEEL CASING JOINTS: WELDED 16 in. to 649 ft., Dia in. to 0 ft., Dia in. to 0 ft. 17 irface 12 in., weight 42 lbs/ft. Wall thickness or gauge No250 18
TYPE OF BLANK CASING USED: Blank casing diameter Casing height above land su TYPE OF SCREEN OR PERFORATION OPENI SCREEN OR PERFORATION OPENI SCREEN PERFORATED INTERVALS GRAVEL PACK INTERVALS GROUT MATERIAL O3 BENTON Grout Intervals: From What is the nearest source Direction from well? FROM : TO : O : 200 : O5 SAND 200 : 220 : O4 SAND 220 : 240 : O7 FINE 240 : 260 : O1 CLAN 260 : 280 : O4 SAND 280 : 300 : O7 FINE 300 : 320 : O5 SAND	O1 STEEL

under the business name of HENKLE DRILLING & SUPPLY

by (signature)

17 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) 08/22/97 and this record is true to the best of my knowledge and belief. Kansas This Water Well Record was completed on (mo/day/yr) 09/04/93

PLY by (signature) Smuf Record was completed on (mo/day/yr) 09/04/93 Water Well Contractor's License No. 145 under the business name of HENKLE DRILLING & SUPPLY