

1 LOCATION OF WATER WELL: County: Stevens	Fraction NW/SE NE/SE NE/SE NE/SE	Section Number 25	Township Number T 34 S	Range Number R 38 EW
--	--	----------------------	---------------------------	-------------------------

Distance and direction from nearest town or city street address of well if located within city?

On Hugoton/Optima Rd & 2nd St. 3W, 1 1/2 N & E into--

2 WATER WELL OWNER: Dave Burrows	RR#, St. Address, Box #: HC-01	City, State, ZIP Code: Hugoton, KS 67951	Board of Agriculture, Division of Water Resources
			Application Number: (620) (316) 544-8250

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 300 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 210 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 210 ft. below land surface measured on mo/day/yr 9/17/92 Pump test data: Well water was 225 ft. after 1 hours pumping 75 gpm Est. Yield 75 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 9 1/2 in. to 300 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 5 in. to 300 ft. Dia. in. to ft. Dia. in. to ft.			Threaded
Casing height above land surface 24 in. weight 2.902 lbs./ft. Wall thickness or gauge No. 280 SDR21			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	9 Drilled holes	
2 Louvered shutter	4 Key punched	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 260 ft. to 300 ft. From 220 ft. to 300 ft.			
GRAVEL PACK INTERVALS: From 40 ft. to 300 ft. From 3.539 ft. to 1 lb./ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other	Hole Plug
Grout Intervals: From 1 ft. to 20 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well?				13 Insecticide storage	
				How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	11	Sandy Clay			
11	16	Sand			
16	38	Clay			
38	73	Sandy Clay			
73	108	Clay			
108	122	Sand & Gravel			
122	183	Brown Clay			
183	194	Sand			
194	202	Brown Clay			
202	211	Sand			
211	218	Brown Clay			
218	296	Sand			
296	300	Yellow Clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/17/92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. KWWCL-430 This Water Well Record was completed on (mo/day/yr) 9/17/92 under the business name of Howard Drlg Co, Box 806 Beaver, OK 73932 by (signature)
--

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.