


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number	
County: Stevens		SW 1/4 NE 1/4 SE 1/4	5	T 34 S	R 38 E(W)	
Distance and direction from nearest town or city street address of well if located within city? From Feterita 1 mi. east on U.S.56 2 3/4 South-1/4 back west into location.						
2 WATER WELL OWNER: Mrs C.E. Carey		Mobil Oil Corp./ Unit #19				
RR#, St. Address, Box #: 533 Stratford		Board of Agriculture, Division of Water Resources				
City, State, ZIP Code: Wichita, Kansas 67206		Application Number: T89-151				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 380 ft. ELEVATION:				
<div style="text-align: center;">N 1 Mile W E S</div> 		Depth(s) Groundwater Encountered 1. 130 ft. 2. ft. 3. ft.				
		WELL'S STATIC WATER LEVEL 130 ft. below land surface measured on mo/day/yr 4-4-89				
		Pump test data: Well water was ft. after hours pumping gpm				
		Est. Yield 100 gpm: Well water was ft. after hours pumping gpm				
Bore Hole Diameter 11 in. to ft., and in. to ft.		WELL WATER TO BE USED AS:				
1 Domestic		3 Feedlot	6 Oil field water supply	8 Air conditioning	11 Injection well	
2 Irrigation		4 Industrial	7 Lawn and garden only	9 Dewatering	12 Other (Specify below)	
Was a chemical/bacteriological sample submitted to Department? Yes.....No X; If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes X No				
5 TYPE OF BLANK CASING USED:		5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped		
1 Steel		3 RMP (SR)	6 Asbestos-Cement	Welded		
2 PVC		4 ABS	7 Fiberglass	Threaded		
Blank casing diameter 6 5/8 in. to 220 ft., Dia. in. to ft., Dia. in. to ft.						
Casing height above land surface 30 in., weight 3.71 lbs./ft. Wall thickness or gauge No. .280						
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC	10 Asbestos-cement			
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)	
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped	8 Saw cut	11 None (open hole)		
1 Continuous slot		3 Mill slot	6 Wire wrapped	9 Drilled holes		
2 Louvered shutter		4 Key punched	7 Torch cut	10 Other (specify)		
SCREEN-PERFORATED INTERVALS: From 220 ft. to 380 ft., From ft. to ft.						
GRAVEL PACK INTERVALS: From 22 ft. to 130 ft., From 140 ft. to 380 ft.						
6 GROUT MATERIAL: 1 Neat cement		2 Cement grout	3 Bentonite	4 Other		
Grout intervals: From 0 ft. to 2 ft., From 2 ft. to 22 ft., From 130 ft. to 140 ft.						
What is the nearest source of possible contamination:		10 Livestock pens	14 Abandoned water well			
1 Septic tank		4 Lateral lines	7 Pit privy	11 Fuel storage		
2 Sewer lines		5 Cess pool	8 Sewage lagoon	12 Fertilizer storage		
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	13 Insecticide storage		
Direction from well? Southwest		How many feet? 175				
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	
0	2	Surface				
2	18	Sandy clay				
18	82	Fine sand				
82	140	Sandy clay				
140	162	50% fine sand-50% sandy clay				
162	230	Sandy clay				
230	263	Med. to large sand				
263	330	Sandy clay				
330	370	50% fine sand-50% sandy clay				
370=	380	Sandy clay				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) April 4, 1989 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 118 This Water Well Record was completed on (mo/day/yr) April 5, 1989 under the business name of Carlile Water Well Service, Inc. by (signature) 