


1 LOCATION OF WATER WELL: County: Stevens		Fraction 1/4 C-SE 1/4 SW 1/4	Section Number 12	Township Number T 34 S	Range Number R 38 EW
Distance and direction from nearest town or city street address of well if located within city limits: From Liberal go West on 2nd St. Road					
2 WATER WELL OWNER: William Rector RR#, St. Address, Box #: Star Route #2 City, State, ZIP Code: Hugoton, Kansas 67951					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 320 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 170 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 150 ft. below land surface measured on mo/day/yr 11/1/82 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 60 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 9 in. to 320 ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded			
Blank casing diameter 5 in. to 260 ft., Dia		in. to ft., Dia			
Casing height above land surface 28 in., weight 2.78 lbs./ft.		Wall thickness or gauge No. 256			
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 9 ABS 12 None used (open hole)		SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 260 ft. to 320 ft.		From ft. to ft.			
GRAVEL PACK INTERVALS: From 140 ft. to 320 ft.		From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other		Grout Intervals: From 0 ft. to 10 ft. From ft. to ft. From ft. to ft.			
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage		Direction from well? West How many feet? 150'			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	surface			
2	24	fine sand			
24	52	sandy clay			
52	65	gravel			
65	85	clay			
85	138	sandy clay			
138	170	medium to large sand			
170	195	clay			
195	210	sandy clay			
210	263	fine sand			
263	275	sandy clay			
275	320	medium to large sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) November 1, 1982 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 118 This Water Well Record was completed on (mo/day/yr) November 17, 1982 under the business name of Carlile Water Well Service, Inc. by (signature) Edward E. Means					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					