

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: STEVENS	SW ¼ SW ¼ NW ¼	28	T 34 S	R 38 W

Distance and direction from nearest town or city street address of well if located within city?

8 WEST AND 8 SOUTH OF HUGOTON, KS.

2 WATER WELL OWNER: MR. GREGORY MORRIS	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : 707 S. POLK	Application Number: 41,513
City, State, ZIP Code : HUGOTON, KS 67951	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 620 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 180. ft. below land surface measured on mo/day/yr 3/12/95 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 26 in. to 620 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) ② Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
① Steel	3 RMP (SR)	6 Asbestos-Cement	Welded <u>X</u>
2 PVC	4 ABS	7 Fiberglass	Threaded
Blank casing diameter 16 in. to 620 ft., Dia in. to ft., Dia in. to ft.			
Casing height above land surface 12 in., weight 42.5 lbs./ft. Wall thickness or gauge No. 250			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
① Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
11 Other (specify)			
12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	③ Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From PERF. 240 ft. to 400 ft., From SCREEN 400 ft. to 440 ft.			
From PERF. 440 ft. to 545 ft., From SCREEN 545 ft. to 565 ft.			
GRAVEL PACK INTERVALS: From 20 ft. to 620 ft., From PERF. 565 ft. to 590 ft.			
From SCREEN 590 ft. to 610 ft., From PERF. 610 ft. to 620 ft.			

6 GROUT MATERIAL:	① Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft.				
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	①⑥ Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	CROPLAND—NOTHING
				IMMEDIATE VICINITY

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	200	SURFACE, SAND & CLAY			
200	260	SANDY BROWN & LIGHT CLAY W/SAND			
260	400	FINE TO MED. SAND			
400	440	FINE TO MED. COARSE SAND & GRAVEL			
440	560	MED. TO COARSE SAND			
560	620	MED. TO COARSE SAND W/REDDISH BROWN CLAY STREAKS			
620	640	RED & BROWN CLAY			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ① constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/11/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 225 This Water Well Record was completed on (mo/day/yr) 3/13/95 under the business name of KTM DRILLING, INC. by (signature) <i>Donald Winters</i>
--