

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Morton		SE 1/4 SE 1/4 NE 1/4		16		T 34 S		R 39 E/W	
Distance and direction from nearest town or city street address of well if located within city? 5 South of Federita 4 West 1/2 North									
2 WATER WELL OWNER: #1 McCalp		Gabbert & Jones		333 E. English St. 215		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Wichita, KS 67202		Application Number: T88-588					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 320 ft. ELEVATION: 12-5-88							
		Depth(s) Groundwater Encountered 1. 120 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 200 ft. below land surface measured on mo/day/yr 12-5-88 Pump test data: Well water was 225 ft. after 2 hours pumping 60 gpm Est. Yield 70 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 9 in. to 320 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No							
		5 TYPE OF BLANK CASING USED:							
		1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded Blank casing diameter 5 in. to 220 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 14 in., weight 200 lbs./ft. Wall thickness or gauge No. 0.265							
		TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)							
SCREEN-PERFORATED INTERVALS:		From 220 ft. to 320 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 190 ft. to 320 ft., From ft. to ft. From ft. to ft., From ft. to ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other		Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? Southwest How many feet? 300							
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS							
0 200 Overburden									
200 220 Medium sand									
220 240 Medium sand									
240 280 Fine sand and clay									
280 300 Medium sand									
300 320 Medium sand and clay									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-5-88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 142 This Water Well Record was completed on (mo/day/yr) 12-7-88 under the business name of T & W Water Well Service, Inc by (signature) [Signature]									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.									