

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <b>MORTON</b>	<b>NW</b> $\frac{1}{4}$ <b>NW</b> $\frac{1}{4}$ <b>NE</b> $\frac{1}{4}$	<b>28</b>	<b>T 34 S</b>	<b>R 40 EW</b>

Distance and direction from nearest town or city street address of well if located within city?

**FROM LIBERAL WEST ON 2nd ST. TO ROLLA JCT. OR 2 WEST, 1 3/4 NORTH, 3/4 WEST, 3/4 NORTH ON TOP HILL.**

2 WATER WELL OWNER: <b>SEABOARD FARM CO.</b>	<b>WELL # 2</b>
RR#, St. Address, Box # <b>BOX 1209</b>	Board of Agriculture, Division of Water Resources
City, State, ZIP Code <b>GYMON, OK 73942</b>	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <b>360</b> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. <b>175</b> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <b>175</b> ft. below land surface measured on mo/day/yr <b>02-12-96</b> Pump test data: Well water was <b>190</b> ft. after <b>1</b> hours pumping <b>100</b> gpm Est. Yield <b>100</b> gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter <b>11</b> in. to <b>360</b> ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only 10 Monitoring well <b>Hog farm</b> Was a chemical/bacteriological sample submitted to Department? Yes No <b>X</b> If yes, mo/day/yr sample was submitted

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <b>X</b> Clamped
1 Steel	3 RMP (SR)	9 Other (specify below)	Welded
<b>2</b> PVC	4 ABS	7 Fiberglass	Threaded
Blank casing diameter <b>6</b> in. to <b>360</b> ft. Dia	in. to ft. Dia	in. to ft. Dia	in. to ft. Dia
Casing height above land surface <b>24</b> in., weight <b>2.902</b> lbs./ft. Wall thickness or gauge No. <b>280 SDR 21</b>			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	9 Drilled holes	
2 Louvered shutter	4 Key punched	10 Other (specify)	
SCREEN-PERFORATED INTERVALS:	From <b>280</b> ft. to <b>360</b> ft.	From ft. to ft.	From ft. to ft.
GRAVEL PACK INTERVALS:	From <b>180</b> ft. to <b>360</b> ft.	From ft. to ft.	From ft. to ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other <b>HOLE PLUG</b>
Grout Intervals: From <b>0</b> ft. to <b>16</b> ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
Direction from well?				How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	TOP SOIL & SAND	287	306	SAND & SANDY CLAY
2	27	SAND	306	319	SAND
27	40	CLAY	319	321	CLAY
40	55	CLAY & SANDY CLAY	321	336	SAND
55	70	CALICHE CLAY	336	350	YELLOW CLAY & SAND STREAKS
70	90	COARSE SAND	350	360	RED
90	100	SANDY CLAY			
100	124	CLAY & SANDY CLAY			
124	148	COARSE SAND			
148	162	CALICHE CLAY			
162	194	SANDY CLAY			
194	218	SAND			
218	235	SANDY CLAY & SAND			
235	265	CLAY & SANDY CLAY			
265	287	SAND			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <b>(1)</b> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <b>02-12-96</b> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <b>KWCL-430</b> This Water Well Record was completed on (mo/day/yr) <b>02-12-96</b> under the business name of <b>HOWARD DRUG CO. BOX 806 BEVAER, OK 73932</b> by (signature) <i>Howard Drug Co.</i>
---