

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: MOKIUN	$\frac{1}{4}$ SW $\frac{1}{4}$ NW $\frac{1}{4}$	18	T 34 S S	R 40W EW

Distance and direction from nearest town or city street address of well if located within city?

FROM ROLA: 4 MILES SOUTHWEST ON 56 & SOUTH INTO LOC.

2 WATER WELL OWNER: SEABOARD FARM CO.	NORTH WELL
RR#, St. Address, Box #: P.O. BOX 1207	Board of Agriculture, Division of Water Resources
City, State, ZIP Code: GUYMON, OK 73942	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 400 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 115 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 115 ft. below land surface measured on mo/day/yr 01-03-96
	Pump test data: Well water was 135 ft. after 1 hours pumping 100 gpm
	Est. Yield 100 gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 11 in. to 400 ft. and in. to ft.
WELL WATER TO BE USED AS:	
5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) HOG FARM 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes X No	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 6 in. to 400 ft. Dia			Threaded
Casing height above land surface 24 in. weight 2.902 lbs./ft. Wall thickness or gauge No. 280 SDR 21			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
SCREEN-PERFORATED INTERVALS: From 300 ft. to 400 ft. From ft. to ft. From ft. to ft. From ft. to ft.			
GRAVEL PACK INTERVALS: From 200 ft. to 400 ft. From ft. to ft. From ft. to ft. From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other HOLE PLUG
GROUT INTERVALS: From 0 ft. to 16 ft. From ft. to ft. From ft. to ft. From ft. to ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? How many feet?				

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	TOP SOIL & SANDY CLAY	248	260	SANDY CLAY & SAND
2	8	SANDY CLAY	260	291	CLAY
8	32	CLAY & CALICHE	291	300	SAND & W/CLAY STREAKS
32	41	COARSE SAND/MED. GRAVEL	300	322	COARSE SAND W/CLAY STREAKS
41	60	CLAY & SANDY CLAY	322	343	COARSE SAND W/YELLOW CLAY STREAKS
60	76	SANDY CLAY	343	387	COARSE SAND
76	90	COARSE SAND	387	397	SAND
90	106	SANDY CLAY	397	400	RED
106	120	SAND			
120	140	COARSE SAND			
140	171	CLAY & SANDY CLAY			
171	183	SAND & SANDY CLAY			
183	204	SAND			
204	234	SANDY CLAY			
234	248	CLAY			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 01-03-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. KWWCL-430 This Water Well Record was completed on (mo/day/yr) 01-03-96 under the business name of HOWARD DRUG CO. BOX 806 BEAVER, OK 73932 by (signature) <i>Howard Drug Co.</i>
