

1 LOCATION OF WATER WELL: County: Morton		Fraction NE ¼ NE ¼ SE ¼	Section Number 36-	Township Number T 34 S	Range Number R 40 EW
Distance and direction from nearest town or city street address of well if located within city? From Rolla - 5½ miles south, 1 mile east, 2,540 ft. north & 50 ft. west					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Boyd Johnson HC02-Box 48 Rolla, Kansas 67954 Board of Agriculture, Division of Water Resources Application Number: 42,551			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL..... 470 ft. ELEVATION:			
<p>Diagram: A square divided into four smaller squares labeled NW, NE, SW, and SE. An 'X' is marked in the center of the SE quadrant.</p>		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 200 ft. below land surface measured on mo/day/yr 11/19/96..... Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter..... 30 in. to 470 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) ② Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No.....X.....; If yes, mo/day/yr sample was sub mitted Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED: ① Steel 3 RMP (SR) 2 PVC 4 ABS		Blank casing diameter 16 in. to 290 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 12 in., weight 42.05 lbs./ft. Wall thickness or gauge No. 250 TYPE OF SCREEN OR PERFORATION MATERIAL: ① Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot ③ Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 290 ft. to 470 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 20 ft. to 470 ft., From ft. to ft. FROM ft. to ft., FROM ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement ② Cement grout 3 Bentonite 4 Other		Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage N/A Direction from well? How many feet?			
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
See attached log					
UNABLE TO PROCURE ATTACHMENT					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ① constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/24/97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/yr) 3/27/97 under the business name of Minter-Wilson Drilling Co., Inc. by (signature) Nora Keller					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					

SEC

RECEIVED
DEC 23 1993
BUREAU OF WATER